

Amended Announcement Follow Up Drilling Confirms Bekajang's 'Multi-Storey' Endowment

This announcement is an amendment of the Announcement released by Besra to the ASX on 6 September 2023, in order to comply with ASX listing Rules 5.23 and 5.16.5 by inserting specific reference to the following:

Besra is not aware of any new information or data that materially affects, in the case of estimates of a Mineral Resource, the material assumptions and technical parameters underpinning its stated Mineral Resource inventory estimates and their related material assumptions and technical parameters continue to apply and have not been materially changed; and

The potential quantity and grade of an Exploration Target is conceptual in nature, there has been insufficient exploration to determine a Mineral Resource and there is no certainty that further exploration work will result in the determination of Mineral Resources or that the production target itself will be realised.

Highlights

- 1,450m drill program to follow up previous high grade gold hit below Bekajang's overlying limestone-shale contact (LSC) in hole BKDDH-27 confirms discrete high grade zone.
- Zone is defined by intense exoskarn development and hydrothermal alteration with highest gold grades, in excess of 10g/t Au, associated with brecciated and veined limestone, cemented by fine grained silica, sulphides and jasperoid replacement.
- Located between ~30m-60m depth, the zone is shallow dipping with a surface footprint currently extending ~150m to the SSW and remains open along strike to the WNW.
- Metal zonation studies highlight the free gold potential of this portion of the Bekajang mineralisation system.
- This drill program also confirms the continuity and tenor of gold mineralisation within the overlying and coincident LSC interval.
- The coincidence of at least two levels of gold mineralisation gives impetus to a further drilling program to identify the source and geometry of the associated hydrothermal conduit system(s) which facilitated this local "multi-storey" endowment.
- Notable assay results from the follow-up round of Bekajang drilling include:
 - BKDDH-32: 8.9m @ 2.43 g/t Au from 50.6 to 59.5m
 - BKDDH-36: 1.0m @ 10.7 g/t Au from 40.7 to 41.7m & 1m @ 5.6 g/t Au from 45.3 to 46.3m
 - BKDDH-37: 1.1m @ 6.25 g/t Au from 6.9 to 8m
 - BKDDH-38: 5.5m @ 3.6 g/t Au from 15.0 to 20.5m
 - BKDDH-39: 1.5m @ 13.03 g/t Au from 56.6 to 58.1m
 - BKDDH-40: 6.2m @ 3.35 g/t Au from 40.7 to 46.9m & 8.5m @ 2.12 g/t Au from 49.8 to 58.3m

- **BKDDH-41:** 1.4m @ **14.21 g/t Au** from 31.5 to 32.9m
 - **BKDDH-42:** 1.0m @ **5.34 g/t Au** from 14.8 to 15.8m
 - **BKDDH-43:** 8.7m @ **1.66g/t Au** from 23to 31.7m.
- **Chemsain Konsultants Sdn Bhd has been engaged to undertake an Environmental Impact Assessment of Bekajang to facilitate representative bulk sampling for processing studies at Besra's Jugan Pilot Plant, once commissioned.**

Interim Chairman, John Seton, commented:

During 2022, we discovered exceptional and bonanza grade gold below the traditional LSC target at Bekajang. Following this up has been the focus of our exploration in 2023 and we are very pleased to report the confirmation of our earlier success, and then some. Assays from this 14-hole program indicate the presence of a potentially very significant understorey of mineral endowment, separate and distinct from that at the overlying LSC level and it remains open along strike. With unparalleled funding capacity for a junior, we intend to exploit these results with further drilling to identify the source of these exceptional gold grades.

Bekajang Follow Up Drilling Program

The follow up program of Bekajang drilling, undertaken during H1 2023, involved 14 fully cored drill holes (BKDDH-31 to -43, 45, inclusive), for a total of 1,450m. It was designed to delineate extensions of the exceptionally high and bonanza gold grade interval intercepted during the first round of drilling in 2022, specifically the interval between 58m-71m in BKDDH-27 (ASX Release on 22 November 2022¹). It was focused on the northern flank of the Bekajang tailings dam (Figure 1). Details of the drill hole specifications for the follow up round are shown on Table 1, as well as in Appendix 2.

Combined both rounds of Besra's Bekajang drilling provide the first comprehensive, fully cored program in the area. Previous reverse circulation (**RC**) drilling delineated gold endowment associated with the shallow Bau Limestone-Pedawan Shale contact, its surface footprint focused along the trace of an interpreted WNW-ESE trending fault. However, the results of BKDDH-27 indicated the presence of a potentially very significant understorey of mineral endowment, separate and distinct from that at the overlying LSC level (Figure 2).

Exceptional gold grades intercepted within the underlying Bau Limestone over the interval 58.4m -71m of BKDDH-27 (Figure 3), included some of the highest (>200 g/t Au) documented since modern exploration commenced within the Bau Gold Field corridor. Together with the very rare occurrence of visible gold, this discovery compelled the need for a follow up round of drilling to evaluate its potential. One interpretation was that this interval represented an intercept or a conduit, part of a feeder system that facilitated net upward vertical access of hydrothermal fluids through the Bau Limestone which then sourced mineral endowment at the overlying LSC interval.

¹ Exceptional High & Bonanza Grade Gold Intercepts Upgrade Bekajang's Potential. Besra ASX Release 22 Nov 2022.




Figure 1: Significant drillhole intercepts from Besra's DDH 2022-2023 programs (black – first round, blue – follow-up round) superimposed onto historical Resource wireframe (in puce) along portion of the northern flank of the Bekajang tailings dam. Section XX' is shown in Figures 3 & 4.

Log for BKDDH-27




Figure 2: Summary of core lithology and gold assay results for BKDDH-27 showing exceptional gold tenor within two distinct intervals; at the LSC and deeper within the Bau Limestone.

As shown on Figure 1, the follow up round of drilling involved a range of azimuths and dips designed to determine not only extensions of this discovery interval but also factors influencing its overall geometry. Figures 3 & 4 illustrate some of the key follow-up round drill results.




Figure 3: Summary of significant intercepts, highlighting the correlation of the discovery interval in BKDDH-27 with assay results from the follow-up round holes (red interval) projected onto cross-section XX'.




Figure 4: Summary of hydrothermal alteration textures used to provide a signature marker for correlating extensions of the BKDDH-27 discovery interval with intercepts from the follow-up round holes (red interval) projected onto cross-section XX'.

Assay Results

Figure 1 shows the location, azimuth and dip of all the follow up round drill holes, which were all fully cored, with a corresponding assay result summary tabulated in Table 1.

Table 1 - Summary of new significant intercepts from the follow up round of the Bekajang drilling program.

| Drill Hole | Primary Target | From (m) | To (m) | Interval (m) | Av Au grade (g/t) |
|------------|----------------|----------|--------|--------------|-------------------|
| BKDDH-32 | LSC | 13.8 | 15.8 | 2.0 | 6.73 |
| BKDDH-32 | Deep Bau | 36.0 | 40.5 | 4.5 | 0.81 |
| BKDDH-32 | Deep Bau | 42.0 | 44.7 | 2.7 | 1.08 |
| BKDDH-32 | Deep Bau | 47.9 | 49.0 | 1.1 | 1.17 |
| BKDDH-32 | Deep Bau | 50.6 | 59.5 | 8.9 | 2.43 |
| BKDDH-33 | Deep Bau | 71.0 | 72.0 | 1.0 | 0.54 |
| BKDDH-34 | Deep Bau | 87.0 | 88.0 | 1.0 | 0.83 |
| BKDDH-36 | Deep Bau | 33.7 | 36.0 | 2.3 | 1.03 |
| BKDDH-36 | Deep Bau | 40.7 | 41.7 | 1.0 | 10.70 |
| BKDDH-36 | Deep Bau | 45.3 | 46.3 | 1.0 | 5.60 |
| BKDDH-37 | LSC | 6.9 | 8.00 | 1.1 | 6.25 |
| BKDDH-37 | LSC | 13.0 | 14.0 | 1.0 | 0.61 |
| BKDDH-37 | LSC | 14.6 | 17.0 | 2.4 | 0.81 |
| BKDDH-37 | Deep Bau | 32.0 | 34.0 | 2.0 | 0.73 |
| BKDDH-37 | Deep Bau | 36.2 | 41.3 | 5.1 | 2.31 |
| BKDDH-37 | Deep Bau | 45.9 | 50.0 | 4.1 | 1.67 |
| BKDDH-37 | Deep Bau | 51.7 | 60.0 | 8.3 | 1.33 |
| BKDDH-38 | LSC | 0.0 | 4.0 | 4.0 | 1.14 |
| BKDDH-38 | LSC | 6.8 | 8.0 | 1.2 | 1.22 |
| BKDDH-38 | LSC | 10.0 | 11.6 | 1.6 | 0.56 |
| BKDDH-38 | LSC | 15.0 | 20.5 | 5.5 | 3.60 |
| BKDDH-39 | Deep Bau | 44.0 | 46.8 | 2.8 | 0.66 |
| BKDDH-39 | Deep Bau | 56.6 | 58.1 | 1.5 | 13.03 |
| BKDDH-40 | LSC | 0.0 | 8.0 | 8.0 | 1.01 |
| BKDDH-40 | LSC | 9.00 | 10.0 | 1.0 | 0.51 |
| BKDDH-40 | Deep Bau | 31.5 | 35.3 | 3.8 | 2.05 |
| BKDDH-40 | Deep Bau | 38.3 | 39.3 | 1.0 | 1.89 |
| BKDDH-40 | Deep Bau | 40.7 | 46.9 | 6.2 | 3.35 |
| BKDDH-40 | Deep Bau | 49.8 | 58.3 | 8.5 | 2.12 |
| BKDDH-41 | LSC | 0.0 | 3.0 | 3.0 | 2.62 |
| BKDDH-41 | LSC | 5.0 | 8.9 | 3.9 | 1.58 |
| BKDDH-41 | LSC | 19.0 | 20.7 | 1.7 | 1.72 |
| BKDDH-41 | Deep Bau | 29.5 | 30.5 | 1.0 | 0.51 |
| BKDDH-41 | Deep Bau | 31.5 | 32.9 | 1.4 | 14.21 |
| BKDDH-41 | Deep Bau | 35.3 | 38.7 | 3.4 | 1.94 |
| BKDDH-41 | Deep Bau | 41.8 | 42.9 | 1.1 | 2.38 |
| BKDDH-41 | Deep Bau | 44.1 | 45.9 | 1.8 | 1.04 |
| BKDDH-42 | LSC | 14.8 | 15.8 | 1.0 | 5.34 |
| BKDDH-43 | LSC | 19.0 | 21.2 | 2.2 | 0.96 |
| BKDDH-43 | LSC | 23.0 | 31.7 | 8.7 | 1.66 |
| BKDDH-43 | Deep Bau | 35.0 | 36.0 | 1.0 | 0.78 |

Results

BKDDH-37, BKDDH-40, BKDDH-41, BKDDH-42 and BKDDH-43 intersected extensions of the discovery interval intercepted in BKDDH-27. Correlation shows the extension to be strata-bound and not steeply dipping and typically located between a depth of 30m-60m. Variations in its intercepted thickness, as illustrated in Figures 3 & 4, reflect proximity to both faulting and intrusives. The follow up round drilling results confirm that this interval is dominated by exoskarn



Figure 5: Hydrothermal alteration with silica dominated replacement in BKDDH-36 at circa 40m depth assaying gold grades of 5.60-10.7g/t Au (top); BKDDH-39 at circa 57m depth assaying gold grades of up to 13.03 g/t Au (middle); BKDDH-41 at circa 32m depth assaying grades of up to 14.21 g/t Au (bottom).

and hydrothermal breccia; best developed along the margins of altered porphyry intrusions or associated with faulting. The highest gold grades are associated with silica alteration and precipitation of crystalline quartz-sulphide in cavities and veins. Figure 5 shows typical alteration styles associated with the higher-grade assay results. In separate studies undertaken for Besra, this alteration is shown to be enriched in Au, Tl, As, Sb, Ag, S and base metals (including Cu Pb and Zn), when compared to the LSC mineralisation. This indicates that mineralisation of the discovery interval of BKDDH-27 is located deeper in standard metal zoning models and therefore more proximal to the originating source. Coupled with the occurrence of free gold in the discovery interval, there is free gold potential in this portion of the Bekajang system associated with this discovery interval and its associated feeder system.

As shown on the cross-sections (Figures 3 & 4), no significant deeper extensions were identified, BKDDH-37 & -40 being drilled through a possible extension of a fault without encountering any significant elevated gold grades, a fault which on the basis of the results of BKDD-27 which considered potentially part of a local feeder system. This leaves unresolved the location and geometry of the underlying feeder conduit system, which is now considered to have locally sourced a multi-storey gold endowment.

Nevertheless, the follow up round results confirm that the discovery interval of BKDDH-27 can be correlated for at least ~150m in a WSW direction, oblique to the surface mapped trace of the WNW fault along which LSC mineralisation trends.

3D modelling of the geometry of the discovery interval, which integrates both the follow up round and historical drilling results, shows it to remain open along strike, in a WNW direction. This is supported by several historical drillholes with significant Au intersections in that direction, highlighting further follow-up opportunity to extend its overall footprint with further drilling (Figure 6).




Figure 6: 3D model showing mineralisation (in red) and potential for possible extension (in grey) together with historical drill holes having significant Au intercepts.

LSC Targets

As shown on Table 1 the follow-up round drilling results continued to confirm the continuity and tenor of gold mineralisation within the overlying LSC. In particular, BKDDH-37, -38, -41 and -42 each encountered significant grades, of up to 6.25g/t Au, at near shallow depths (<20m), where the Pedawan Shale or “Z” horizon is developed.

Environmental Impact Assessment

Chemsain Konsultant Sdn Bhd has been engaged to undertake an Environmental Impact Assessment (EIA) of Bekajang in order for Besra to commence mining activities for representative bulk sampling and conduct processing studies at Besra’s Jugan Pilot Plant, once commissioned. This plant lies approximately 6 km to the NE and is connected by all-weather roads.

Chemsain has indicated that the EIA will take approximately 3 months to complete, on the basis that it will follow guidelines and procedures established during the earlier Jugan EIA which it also prepared on Besra’s behalf.

This announcement has been approved by the Board of Besra.

For further information:

Australasia

Ray Shaw

Chief Technical Officer

Email: ray.shaw@besra.com

North America

James Hamilton

Investor Relations Services

Mobile: +1 416 471 4494

Email: jim@besra.com

Overview of Bau Gold Field & Bekajang Project

The Bau Gold Field corridor is located 30km - 40km from Kuching, the capital city of the State of Sarawak, Malaysia, at the western end of an arcuate metalliferous belt extending through the island of Borneo. In Kalimantan, the Indonesian jurisdiction portion of Borneo, this belt is associated with significant gold mining, including Kelian (7 Moz) and Mt Muro (3 Moz). The Bau Gold Field is defined by a gold mineralisation system covering approximately an 8km x 15km corridor, centred on the township of Bau (Figure 7). Within this corridor Besra has identified classified JORC (2012) Resources of Measured 3.4 Mt @ 1.5g/t Au for 166.9koz, Indicated 16.4 Mt @ 1.57g/t Au for 824.8 koz and Inferred 47.9 Mt @ 1.29 g/t Au for 1,989 koz, across a number of discrete deposits (refer to the Company’s Prospectus dated 8 July 2021 – Section 3.11). In addition to the JORC-2012 Mineral Resource, the project has a global Exploration Target of between 4.89 and 9.27m ounces of gold @ 1.7–2.5 g/t Au (on a 100% basis). The potential quantity and grade of an Exploration Target is conceptual in nature, there has been insufficient exploration to determine a Mineral Resource and there is no certainty that further exploration work will result in the determination of Mineral Resources or that the production target itself will be realised.

Besra is not aware of any new information or data that materially affects, in the case of estimates of a Mineral Resource, the material assumptions and technical parameters underpinning the above Mineral Resource estimates and those material assumptions and technical parameters continue to apply and have not been materially changed.

The Bekajang Project lies along a very prospective trend that includes two historical mine sites (Figure 8). The Bukit Young Gold pit (BYG) was mined until September 1992, prior to the redevelopment of Tai Parit that, according to mine records, produced some 440,926 tonnes at a

grade of 4.51 g/t Au. Tai Parit recorded production of some 700,000 oz of gold, of which approximately 213,000 oz @ 7 g/t was produced between 1991 and 1997 by Bukit Young Gold Mine Sdn Bhd, the last commercial operator in the region. Historical drilling provides the basis for a substantial JORC 2012 compliant Resource inventory at Bekajang, comprising:

- a Measured and Indicated Resource totalling 120.4 koz @ 2.0 g/t Au and an Inferred Resource of 524 koz @ 1.5 g/t Au (refer to the Company's Prospectus dated 8 July 2021 – Section 3.11); and
- an additional Exploration Target of 0.50 – 0.80 Moz @ 2.0 – 3.0 g/t Au, respectively.

Besra is not aware of any new information or data that materially affects, in the case of estimates of a Mineral Resource, the material assumptions and technical parameters underpinning the above Mineral Resource estimates and those material assumptions and technical parameters continue to apply and have not been materially changed.

The potential quantity and grade of an Exploration Target is conceptual in nature, there has been insufficient exploration to determine a Mineral Resource and there is no certainty that further exploration work will result in the determination of Mineral Resources or that the production target itself will be realised.




Figure 7: Location of the Bekajang Sector (highlighted within red box) south Bau township in the centre of the Bau Gold Field corridor and adjacent to the most recent commercial mine Tai Parit.




Figure 8: Location of the prospective Bekajang – Bukit Young – Tai Parit trend showing Resource wire-frames (in purple) and the Bekajang drilling core hole locations (blue annotation). Detailed illustration of the area contained within the purple rectangle is shown as Figure 1.

Competent Person's Statement

The information in this announcement that relates to Exploration Results, Mineral Resources or Ore Reserves is based on information compiled by Mr. Kevin J. Wright, a Competent Person who is a Fellow of the Institute of Materials, Minerals and Mining (FIMMM), a Chartered Engineer (C.Eng) and a Chartered Environmentalist (C.Env). Mr. Wright is a consultant to Besra. Mr. Wright has sufficient experience which is relevant to the style of mineralisation and type of deposit under consideration and to the activity which he is undertaking to qualify as a Competent Person as defined in the JORC Code (2012 Edition) of the Australasian Code for Reporting of Exploration Results and a Qualified Person as defined in National Instrument 43-101 Standards of Disclosure for Mineral Projects of the Canadian Securities Administrators.

Kevin J. Wright consents to the inclusion in this Announcement of the matters based on his information in the form and context that it appears.

Disclaimer

This announcement contains certain forward-looking statements and forecasts concerning future activities, including potential delineation of resources. Such statements are not a guarantee of future performance and involve unknown risks and uncertainties, as well as other factors which are beyond the control of Besra Gold Inc. Actual results and developments may differ materially from those expressed or implied by these forward-looking statements depending upon a variety of factors. Nothing in this announcement should be construed as either an offer to sell or a solicitation of an offer to buy or sell securities.

This announcement has been prepared in accordance with the requirements of Australian securities laws and the requirements of the Australian Securities Exchange and may not be released to US wire services or distributed in the United States. This announcement does not constitute an offer to sell, or a solicitation of an offer to buy, securities in the United States or any other jurisdiction. Any securities described in this announcement have not been, and will not be, registered under the US Securities Act of 1933 and may not be offered or sold in the United States except in transactions exempt from, or not subject to, registration under the US Securities Act and applicable US state securities laws.

Unless otherwise indicated, all mineral resource estimates and Exploration Targets included or incorporated by reference in this announcement have been, and will be, prepared in accordance with the JORC classification system of the Australasian Institute of Mining and Metallurgy and Australian Institute of Geoscientists.

Ownership Interest in Bau

Besra is in a consortium with a Malaysian group with Bumiputra interests that owns rights to consolidated mining tenements covering much of the historic Bau goldfield in Sarawak, East Malaysia. Besra's interests in the Bau Gold Project are held through its direct and indirect interests in North Borneo Gold Sdn Bhd ("**NBG**"). Besra's 100% owned subsidiary - Besra Labuan Ltd ("**Besra Labuan**")- acquired its interest in NBG, which owns rights to the mining tenements covering the area of Bau in accordance with various agreements the sale of shares (refer to Prospectus dated 8 July 2021, sections 3, 8.4 and Attachment H) as a result of which Besra's interests in NBG increased to 97.8% and its equity adjusted interest increased to 92.8%.

Disclosure

The Pejiru Sector lies within MC/KD/01/1994 which has been pending renewal for several years. As outlined in the Malaysian Solicitor's Report on Title (Attachment G) of the Replacement Prospectus of Besra dated 8 July 2021, until a decision is made, the intention of section 48(9) of the Minerals Ordinance is to enable mining activities to continue on a pre-existing licence, in those prior lands of MC/KD/01/1994, until a determination of the renewal is made.

The information in this announcement is based on the following publicly available announcements previously lodged on the SEDAR Company Information Besra Gold Inc platform or on Besra's website:

- Besra Gold Inc Bau Gold Project Sarawak Malaysia Exploration Target Inventory. Lodged SEDAR Platform Feb 26, 2021; and
- Besra Bau Project – Mineral Resource and Ore Reserve Updated to JORC 2012 Compliance. Lodged SEDAR Platform Nov 22, 2018.



Besra (Accipiter virgatus), also called the besra sparrowhawk, occurs throughout southern and eastern Asia. It is a medium sized raptor with short broad wings and a long tail making it very adept at manoeuvring within its environment and an efficient predator.

**APPENDIX 1: SIGNIFICANT INTERVALS OF ASSAYS REPORTED FOR
BEKAJANG BKDDH DRILL HOLES***

(*Follow-up Round assay results highlighted in yellow)

| Drill Hole | Primary Target | From (m) | To (m) | Interval (m) | Av Au grade (g/t) |
|------------|----------------|----------|--------|--------------|-------------------|
| BKDDH-12 | LSC | 0 | 2.0 | 2.0 | 1.26 |
| BKDDH-12 | LSC | 4.0 | 7.0 | 3.0 | 3.13 |
| BKDDH-13 | LSC | 0.0 | 1.0 | 1.0 | 2.08 |
| BKDDH-13 | LSC | 7.0 | 10.6 | 3.6 | 14.68 |
| Including | LSC | 12.3 | 13.6 | 1.3 | 37.00 |
| Including | LSC | 9.0 | 10.0 | 1.0 | 37.2 |
| BKDDH-14A | LSC | 6.0 | 12.7 | 6.7 | 3.34 |
| BKDDH-14A | LSC | 21.0 | 24.0 | 3.0 | 4.65 |
| BKDDH-15 | LSC | 13.7 | 14.4 | 0.7 | 14.1 |
| BKDDH-16 | LSC | 18.0 | 22.2 | 1.42 | 4.20 |
| BKDDH-18 | LSC | 2.4 | 4.8 | 2.4 | 2.35 |
| BKDDH-18 | LSC | 28.4 | 29.0 | 0.9 | 1.73 |
| BKDDH-18 | LSC | 33.0 | 35.0 | 2.0 | 1.19 |
| BKDDH-18 | LSC | 41.0 | 44.1 | 3.1 | 1.20 |
| BKDDH-19 | LSC | 38.7 | 43.0 | 4.3 | 0.81 |
| BKDDH-22 | LSC | 9.0 | 12.75 | 3.75 | 0.77 |
| BKDDH-23 | LSC | 1.0 | 9.0 | 8.0 | 1.35 |
| BKDDH-23 | LSC | 19.4 | 28 | 8.6 | 17.71 |
| including | LSC | 19.4 | 20.0 | 0.6 | 30.4 |
| Including | LSC | 20.0 | 20.8 | 0.8 | 103.0 |
| BKDDH-25 | Bau Deep | 65.0 | 68.7 | 3.7 | 0.86 |
| BKDDH-25 | Bau Deep | 71.6 | 76.0 | 4.4 | 0.82 |
| BKDDH-25 | Bau Deep | 86.0 | 86.9 | 0.9 | 3.17 |
| BKDDH-26 | Bau Deep | 48.0 | 50.0 | 2.0 | 0.73 |
| BKDDH-27 | LSC | 0.0 | 2.0 | 2.0 | 1.20 |
| BKDDH-27 | LSC | 8 | 17.7 | 9.7 | 7.09 |
| Including | LSC | 15.1 | 16.0 | 0.9 | 39.3 |
| BKDDH-27 | Bau Deep | 40.3 | 42.0 | 1.7 | 8.81 |
| BKDDH-27 | Bau Deep | 43.6 | 45.0 | 1.4 | 4.49 |
| BKDDH-27 | Bau Deep | 53.9 | 56.1 | 2.2 | 3.90 |
| BKDDH-27 | Bau Deep | 58.4 | 71.0 | 12.6 | 22.91 |
| Including | Bau Deep | 60.5 | 61.0 | 0.5 | 209.0 |
| Including | Bau Deep | 61.0 | 62.0 | 1.0 | 64.0 |
| Including | Bau Deep | 62.0 | 63.0 | 1.0 | 15.9 |
| Including | Bau Deep | 63.0 | 64.0 | 1.0 | 31.8 |
| Including | Bau Deep | 64.0 | 65.0 | 1.0 | 22.3 |
| Including | Bau Deep | 67.0 | 68.0 | 1.0 | 14.1 |
| BKDDH-28 | LSC | 11.0 | 17.7 | 6.7 | 6.49 |
| Including | LSC | 15.0 | 16.0 | 1.0 | 28.6 |
| BKDDH-29 | LSC | 26.0 | 35.0 | 9.0 | 3.22 |

| | | | | | |
|-----------|----------|-------|-------|------|-------|
| Including | LSC | 28.0 | 30.0 | 2.0 | 6.5 |
| BKDDH-29 | Bau Deep | 36.0 | 39.0 | 0.55 | 3.0 |
| BKDDH-29 | Bau Deep | 40.0 | 44.0 | 4.0 | 0.87 |
| BKDDH-30 | LSC | 20.85 | 22.0 | 1.15 | 1.72 |
| BKHHD-30 | LSC | 25.0 | 26.0 | 1.0 | 2.25 |
| BKDDH-32 | LSC | 13.8 | 15.8 | 2.0 | 6.73 |
| BKDDH-32 | Bau Deep | 36.0 | 40.5 | 4.5 | 0.81 |
| BKDDH-32 | Bau Deep | 42.0 | 44.7 | 2.7 | 1.08 |
| BKDDH-32 | Bau Deep | 47.9 | 49.0 | 1.1 | 1.17 |
| BKDDH-32 | Bau Deep | 50.6 | 59.5 | 8.9 | 2.43 |
| BKDDH-33 | Bau Deep | 71.0 | 72.0 | 1.0 | 0.54 |
| BKDDH-34 | Bau Deep | 87.0 | 88.0 | 1.0 | 0.83 |
| BKDDH-36 | Bau Deep | 33.7 | 36 | 2.3 | 1.03 |
| BKDDH-36 | Bau Deep | 40.7 | 41.7 | 1.0 | 10.70 |
| BKDDH-36 | Bau Deep | 45.3 | 46.3 | 1.0 | 5.60 |
| BKDDH-37 | LSC | 6.90 | 8.0 | 1.1 | 6.25 |
| BKDDH-37 | LSC | 13.0 | 14.0 | 1.0 | 0.61 |
| BKDDH-37 | LSC | 14.6 | 17.0 | 2.4 | 0.81 |
| BKDDH-37 | Bau Deep | 32.0 | 34.0 | 2.0 | 0.73 |
| BKDDH-37 | Bau Deep | 36.2 | 41.3 | 5.1 | 2.31 |
| BKDDH-37 | Bau Deep | 45.9 | 50.0 | 4.1 | 1.67 |
| BKDDH-37 | Bau Deep | 51.7 | 60.0 | 8.3 | 1.33 |
| BKDDH-38 | LSC | 0.0 | 4.0 | 4.0 | 1.14 |
| BKDDH-38 | LSC | 6.8 | 8.0 | 1.2 | 1.22 |
| BKDDH-38 | LSC | 10.0 | 11.6 | 1.6 | 0.56 |
| BKDDH-38 | LSC | 15.0 | 20.5 | 5.5 | 3.60 |
| BKDDH-39 | Bau Deep | 44.0 | 46.8 | 2.8 | 0.66 |
| BKDDH-39 | Bau Deep | 56.6 | 58.1 | 1.5 | 13.03 |
| BKDDH-40 | LSC | 0.0 | 8.0 | 8.0 | 1.01 |
| BKDDH-40 | LSC | 9.0 | 10.0 | 1.0 | 0.51 |
| BKDDH-40 | Bau Deep | 31.5 | 35.3 | 3.8 | 2.05 |
| BKDDH-40 | Bau Deep | 38.3 | 39.3 | 1.0 | 1.89 |
| BKDDH-40 | Bau Deep | 40.70 | 46.90 | 6.2 | 3.35 |
| BKDDH-40 | Bau Deep | 49.80 | 58.30 | 8.5 | 2.12 |
| BKDDH-41 | LSC | 0.0 | 3.0 | 3.0 | 2.62 |
| BKDDH-41 | LSC | 5.0 | 8.9 | 3.9 | 1.58 |
| BKDDH-41 | LSC | 19.0 | 20.7 | 1.7 | 1.72 |
| BKDDH-41 | Bau Deep | 29.5 | 30.5 | 1.0 | 0.51 |
| BKDDH-41 | Bau Deep | 31.5 | 32.9 | 1.4 | 14.21 |
| BKDDH-41 | Bau Deep | 35.3 | 38.7 | 3.4 | 1.94 |
| BKDDH-41 | Bau Deep | 41.8 | 42.9 | 1.1 | 2.38 |
| BKDDH-41 | Bau Deep | 44.1 | 45.9 | 1.8 | 1.04 |
| BKDDH-42 | LSC | 14.8 | 15.8 | 1.0 | 5.34 |
| BKDDH-43 | LSC | 19.0 | 21.2 | 2.2 | 0.96 |
| BKDDH-43 | Bau Deep | 23.0 | 31.7 | 8.7 | 1.66 |
| BKDDH-43 | Bau Deep | 35.0 | 36.0 | 1.0 | 0.78 |

APPENDIX 2: DRILL HOLE SPECIFICATIONS FOR BEKAJANG DDH PROGRAM 2021-2022.

| Hole ID | Project | Easting | Northing | Elevation | Declin. | Azimuth | Depth |
|-----------|----------|-----------|-----------|-----------|---------|---------|-------|
| BKDDH-12 | Bekajang | 406418.4 | 155754.0 | 38.2 | -90 | 0 | 60.4 |
| BKDDH-13 | Bekajang | 406457.6 | 155717.5 | 33.0 | -90 | 0 | 60.0 |
| BKDDH-14 | Bekajang | 406411.4 | 155730.8 | 39.9 | -90 | 0 | 24.2 |
| BKDDH-14A | Bekajang | 406409.4 | 155730.0 | 39.9 | -90 | 0 | 54.5 |
| BKDDH-15 | Bekajang | 406466.0 | 155736.9 | 37.0 | -90 | 0 | 50.0 |
| BKDDH-16 | Bekajang | 406635.7 | 155741.2 | 30.5 | -90 | 0 | 63.2 |
| BKDDH-17 | Bekajang | 406840.0 | 155619.2 | 28.4 | -90 | 0 | 52.2 |
| BKDDH-18 | Bekajang | 406614.3 | 155705.2 | 32.2 | -90 | 0 | 50.1 |
| BKDDH-19 | Bekajang | 406794.8 | 155645.8 | 28.8 | -90 | 0 | 50.4 |
| BKDDH-20 | Bekajang | 406673.1 | 155697.0 | 28.3 | -90 | 0 | 24.3 |
| BKDDH-20A | Bekajang | 406677.6 | 155694.3 | 28.4 | -90 | 0 | 21.0 |
| BKDDH-21 | Bekajang | 406716.1 | 155675.7 | 29.5 | -90 | 0 | 27.3 |
| BKDDH-22 | Bekajang | 406748.1 | 155665.0 | 28.0 | -90 | 0 | 50.5 |
| BKDDH-23 | Bekajang | 406655.3 | 155691.6 | 30.8 | -90 | 0 | 50.1 |
| BKDDH-24 | Bekajang | 406299.7 | 155303.5 | 41.9 | -60 | 360 | 110.8 |
| BKDDH-25 | Bekajang | 406276.9 | 155309.7 | 50.8 | -60 | 360 | 121.9 |
| BKDDH-26 | Bekajang | 406403.8 | 155756.8 | 38.3 | -60 | 200 | 100.1 |
| BKDDH-27 | Bekajang | 406486.4 | 155729.7 | 34.3 | -60 | 200 | 102.5 |
| BKDDH-28 | Bekajang | 406634.3 | 155716.2 | 29.3 | -70 | 200 | 102.2 |
| BKDDH-29 | Bekajang | 406670.4 | 155693.6 | 28.4 | -70 | 200 | 117.2 |
| BKDDH-30 | Bekajang | 406403.8 | 155756.8 | 38.3 | -60 | 200 | 109.8 |
| BKDDH-31 | Bekajang | 406388.2 | 55739.247 | 38.6 | -60 | 315 | 70.1 |
| BKDDH-32 | Bekajang | 406393.4 | 55713.745 | 39.2 | -70 | 315 | 84.5 |
| BKDDH-33 | Bekajang | 406407.6 | 55757.097 | 38.2 | -60 | 315 | 114.2 |
| BKDDH-34 | Bekajang | 406422.2 | 55682.053 | 33.0 | -60 | 315 | 130.3 |
| BKDDH-35 | Bekajang | 406356.8 | 55767.490 | 36.2 | -70 | 135 | 99.8 |
| BKDDH-36 | Bekajang | 406394.0 | 55714.881 | 39.1 | -60 | 30 | 107.4 |
| BKDDH-37 | Bekajang | 406368.7 | 55676.906 | 31.8 | -60 | 30 | 131.4 |
| BKDDH-38 | Bekajang | 406418.8 | 55707.837 | 32.4 | -60 | 30 | 100.1 |
| BKDDH-39 | Bekajang | 406374.6 | 55732.854 | 38.8 | -60 | 30 | 110.8 |
| BKDDH-40 | Bekajang | 406368.8 | 55678.599 | 31.7 | -70 | 30 | 151.3 |
| BKDDH-41 | Bekajang | 406355.0 | 55656.896 | 31.4 | -75 | 30 | 94.4 |
| BKDDH-42 | Bekajang | 406343.9 | 55689.286 | 31.3 | -70 | 30 | 72.1 |
| BKDDH-43 | Bekajang | 405945.47 | 155679.43 | 30.69 | -70 | 30 | 78.0 |
| BKDDH-45 | Bekajang | 405896.89 | 155607.56 | 31.73 | -60 | 30 | 102.3 |

JORC Code, 2012 Edition – Table 1.

Section 1 Sampling Techniques and Data

(Criteria in this section apply to all succeeding sections)

| Criteria | JORC Code explanation | Commentary |
|----------------------------|--|---|
| Sampling techniques | Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling. | <p>BESRA. HQ sized (63mm) diamond drill (DD) core was sampled using a diamond saw to cut the cores in half. Samples were collected at 1m intervals.</p> <p>Historically at Bekajang a combination of reverse circulation (RC) and diamond drilling (DD) has been used.</p> <p>Pre-1993 drill sampling at Bekajang by Bukit Young Goldmines was mostly BQ (36mm) and some NQ (48mm) diamond core. Cores were split in half, by placing the cores in a carousel and splitting the core using a hammer and masonry chisel. Sample intervals were typically 1.5 to 2m intervals but selected intervals ranged from 0.5 to 2.55m.</p> <p>Pre-1993 diamond drilling by RGC and Gencor was HQ sized and split using a core saw.</p> <p>1993 - 2000 Menzies Gold NL (Menzies). RC samples were collected in plastic bags at 1m intervals from the cyclone (~25kg). Samples were split using a 4-inch diameter tube “spear” and placed into another 1m sample bag from which a second split was collected using a 2-inch spear. These second splits were composited into 4m intervals of around 1 to 4 kg from which 30g to 50g was used for All sample bags were appropriately labelled, ticketed and documented. When composite results assayed greater than 0.5 Au g/t, the original 1m samples were re-assayed.</p> <p>Diamond core samples were HQ triple tube reducing to NQ where ground conditions required. Core holes for metallurgical samples were drilled PQ (85mm) size. Samples were collected at 1m intervals in mineralization and 4m intervals outside of mineralization. 4m samples were collected using a core grinder that cut a “fillet” from the side of the core creating a 100 – 200g sample of fine powder for assay. 1m samples were split in half using a core saw.</p> <p>North Borneo Gold (NBG) 2005 – 2012. Drill sampling was HQ triple tube with PQ3 collars. Cores were reduced to NQ triple tube when poor ground conditions were encountered. Cores were split in half using a diamond saw. Samples were typically collected at 1m intervals. Some sample intervals were shortened or lengthened to stay within mineralized or lithological boundaries</p> |

| Criteria | JORC Code explanation | Commentary |
|----------------------------|---|--|
| | <p>Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used.</p> <p>Aspects of the determination of mineralization that are Material to the Public Report. In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralization types (e.g. submarine nodules) may warrant disclosure of detailed information.</p> | <p>For all diamond drilling, core recoveries were recorded on sample record sheets and entered into a database.</p> <p>For all RC drilling, wet samples were recorded and all 1m samples weighed as a check against recoveries. Field duplicates were collected routinely using the sample spear as a cross check for sampling errors.</p> <p>All DD core and RC holes drilled at Bekajang have been geologically logged and sampled in their entirety.</p> <p>Mineralization at Bekajang is fine grained and disseminated throughout the host sediment. No nugget effect or unusual mineralization styles that may cause sampling problems have been encountered.</p> <p>Post 2005 (NBG/BESRA) all diamond half core were sent to accredited labs for assay. All samples were pulverized and a 30g or 50g charge was prepared for fire assay. Samples were also routinely assayed for elements closely associated with the gold mineralization i.e. arsenic, antimony, iron, sulphur, by ICP.</p> <p>Pre-1993 (BYG) half core samples were analysed for gold only at the Tai Parit mine site lab, initially by AAS and later by fire assay.</p> <p>Pre-1993 Gencor and RGC half core samples were partly analysed at the BYG mine lab and partly analysed at commercial labs offshore.</p> <p>1993 – 2000 Menzies. 1m half core and 1m RC samples (2-3kg) of mineralization were dried, crushed and pulverized on site before being sent to Assaycorps lab in Kuching for fire assay. Four metre core samples from outside the mineralized interval were sampled using a core grinder that cuts a groove in the core a creates a 100-200g sample of powder. Four metre composite samples of unmineralized material were made up from 1m RC samples using a PVC spear.</p> |
| Drilling techniques | <p>Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).</p> | <p>BESRA. Drilling completed at Jugan by Besra consisted of HQ triple tube diamond core drilling. Two rigs have been contracted from Drillcorp (Malaysia) Sdn Bhd, a skid mounted custom-made rig and a track mounted G&K 850. Core orientation is being conducted where core conditions permit using a Champ Ori 'OriShot' orientation device.</p> <p>Down hole surveys were conducted at 20m intervals using a Camteq 'ProShot' electronic multi-shot camera.</p> <p>Pre-1993 (BYG) core drilling at Jugan and Bekajang was conducted using a man</p> |

| Criteria | JORC Code explanation | Commentary |
|------------------------------|---|--|
| | | <p>portable Winkie drill, Longyear 28 and Korean rig. Cores produced ranged from BQ (36mm) to HQ (48mm) size. No core orientation surveys were conducted.</p> <p>Pre-1993 Gencor and RGC, core drilling was conducted using a Longyear 44.</p> <p>1993-2000 (Menziess) RC drilling was completed using a Schramm T4 rig using a 6" face sampling bit. Diamond drilling was conducted using a Boart Longyear 44 skid mounted rig. Core orientations were made in the angled diamond holes using a spear tipped with a crayon.</p> <p>2010 – 2012 (NBG) used Indodrill ID 500 track/skid mounted rigs drilling between 100-200 metres depth with dips between 90 and 40 degrees from horizontal. All NBG drilling was DD with triple tube; angled and orientated; drill core used was HQ3 with PQ3 collars. NQ3 was only used when poor ground conditions dictated; metallurgical holes were drilled with PQ3/PQ.</p> <p>All DD core where geological conditions allowed, were oriented at the end of each 3m run. Early in the program this was achieved by an orientation spear and then progressed to the use of an electronic 'OriShot' orientation device. The drillers mark the base of the drill core at the end of the run and marked the base line of the core axis. This was checked by the NBG site geologist for accuracy and consistency.</p> <p>All NBG drill holes were initially routinely surveyed with a HKCX single shot down hole camera then replaced by a Cameq 'ProShot' electronic multi-shot camera. Readings were taken every 25m down hole for all holes and surveyed at termination.</p> <p>Down hole surveys were checked mathematically and visually in the database, and in 3D in the CAE Mining Studio geological and mining software package. Any surveys with recorded errors of unacceptable deviations were excluded from the down hole survey database.</p> <p>Historic drill holes did not have down hole surveys done, only drill hole orientations surveyed at the collar. Most of the holes were shallow (<100m) and vertical. Deviation is considered minor.</p> |
| Drill sample recovery | <p>Method of recording and assessing core and chip sample recoveries and results assessed.</p> <p>Measures taken to maximise sample recovery and ensure representative nature of the samples.</p> | <p>BESRA. HQ triple tube drilled at Bekajang to maximise core recoveries. Cores are systematically logged by geologists with detailed lithological and geotechnical information, including recoveries, recorded on written logs which is then transferred to a database.</p> |

| Criteria | JORC Code explanation | Commentary |
|----------|---|--|
| | <p>Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.</p> | <p>Mineralization is finely disseminated throughout the host rock and no bias has been recognised between recovery and grade.</p> <p>Pre-1993, BYG, Gencor and RGC, core recoveries were recorded on hard copy logs. Data collected by Gencor and RGC was transferred to digital databases.</p> <p>1993 – 2000 (Menziess). During RC drilling weights of 1m samples collected from under the cyclone were recorded so that recoveries could be monitored. Most RC holes were shallow (<100m) and samples were dry.</p> <p>The sample return hose and cyclone were systematically cleaned at each rod change to minimize sample contamination. Sampling equipment was cleaned after each sample was taken.</p> <p>For diamond drilling core recoveries were recorded during logging and averaged better than 95%.</p> <p>DD core is firstly measured on a run-by-run basis and marked out in 1m intervals. Core recoveries were documented and any discrepancies between drill runs as recorded and measured were rectified. Field logs were completed to include measured core recovery at the rig before transporting the core in secured tray boxes to the Menziess sampling facility.</p> <p>Where difficult ground was encountered or where the sample recovery could be compromised controlled drilling speeds and short drilling runs were requested.</p> <p>2005 – 2012 (NBG) diamond drilling, each drill run was recorded in a log that was signed by the drill contractor and NBG's representative each day.</p> <p>The 2010 Feasibility Study by Terra Mining Consultants/ Stevens & Assoc. (TMCSA) stated no bias between recoveries and gold grade was identified.</p> <p>The drilling contractor's agreement with NBG was structured to ensure that the maximum possible core recovery was achieved, with reasonable precautions being taken to prevent crushing, wearing or grinding of the core. Core loss deemed to be due to the Contractor's negligence was not paid and when excessive in the opinion of the Company, necessitated re-drilling.</p> <p>Driller was committed to apply the minimum force to liberate the core from the core barrel and make a minimum number of breaks in the core to enable fitting into trays.</p> <p>Each tray had blocks indicating the hole number and estimated depth, at both the start and end of the tray as well as measured rod depth at the end of each drill run, irrespective of the length of the run.</p> |

| Criteria | JORC Code explanation | Commentary |
|----------------|--|--|
| | | <p>A block was placed at the end of the run showing the measured rod depth and the amount of core lost had the subscript "L/C". A block also showing nominal depth at the start of a run wherein a core orientation survey was taken had the subscript "C.O.".</p> <p>Orientation of all competent HQ and NQ core was conducted down hole by the Contractor as required by the Company.</p> <p>Cores misplaced, spilt or otherwise rendered unusable owing to the Contractor's acts or omissions necessitated re-drilling</p> <p>As can best be determined from historic accounts and recent reporting, measures taken during drilling were aimed at maximising sample recovery to ensure representativity of all samples.</p> |
| Logging | <p>Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.</p> | <p>BESRA. Current core logging practices follow strict procedures put in place by NBG in 2010. Detailed lithology, alteration, vein and structure densities and types are recorded on a run-by-run basis. Structural readings are collected where core orientation surveys allowed.</p> <p>Detailed geotechnical data is also recorded, such as recovery, rock quality designation index (RQD), weathering intensity, core hardness, etc.</p> <p>Logging information is collected on hard copy sheets then transferred into databases.</p> <p>Pre-2000, BYG, Gencor, RGC and Menzies logged and sampled core, which they documented in hardcopy, transferring to digital format.</p> <p>All the Menzies RC holes were geologically logged and codes assigned on hardcopy logs. Data was manually entered and for the most part was systematically and accurately done.</p> <p>TMCSA which undertook the Bau Project - 2013 Pre-feasibility Study, stated that historic drill core logging data in hardcopy included geological descriptions, and sample intervals correlating to assay data represented that procedures had followed the accepted standard at the time.</p> <p>TMCSA also managed the review and re-logging/re-interpretation of historic core where appropriate and their observations showed that all previous companies undertook geological logging with adequate geological descriptions, sample intervals marked, and correlated to assay data, concluding that systematic procedures were followed in most cases to the acceptable standards at the time.</p> |

| Criteria | JORC Code explanation | Commentary |
|----------|-----------------------|--|
| | | <p>In 2010, representative drill core from Jugan used in the Mineral Resource estimation were reviewed by TMCSA, comparing drill core with lithological descriptions in the drill logs and checked against the lithological data entered into the database.</p> <p>Hardcopy core logging was generally descriptive by all companies that have to date worked at Bau. BYG, Menzies and RGC coded on hardcopy logs then entered into the geological databases.</p> <p>Recoveries were measured and geotechnically logged by a qualified geologist in hardcopy logs after which the data was electronically entered in the database. For RC chip samples, Menzies entered the geological descriptions onto hardcopy logs which TMCSA reviewed and found generally consistent with geological descriptions essentially correlating with geochemistry.</p> <p>TMCSA was satisfied that the core logging had been carried out and the data recorded and entered into the database to accepted industry standards and that the logging supported geological continuity, and was able to define appropriate domains, based on geology for resource estimates.</p> <p>2005 – 2012 NBG core drilling followed the NBG logging and data validation procedures.</p> <p>Geotechnical observations of weathering, Rock Quality Designation (RQD), discontinuity types and frequency per metre were logged.</p> <p>Geomechanical logging by a geotechnical engineer determined Rock Mass Rating (RMR) and other geomechanical factors for the cores of JUDDH-06 to JUDDH-81. While the geological logging was largely based on the lithology, alteration and mineralization, veining and structures; the geomechanical logging was based on a maximum length of 3m per run and considered the mechanical, structural and the mineralogical properties of the rocks and rated them according to the Rock Mass Rating (RMR) parameters.</p> <ul style="list-style-type: none"> o Rock Quality Designation (RQD) based on: <ul style="list-style-type: none"> a. Recovered length; b. Length of run. o Discontinuity per metre based on: <ul style="list-style-type: none"> c. Total number of discontinuities; d. Recovered length of run. o Discontinuity roughness. |

| Criteria | JORC Code explanation | Commentary |
|----------|---|---|
| | <p>Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography.</p> | <ul style="list-style-type: none"> o Discontinuity alteration and fill based on: <ul style="list-style-type: none"> e. Infill and mineralization in the infill; f. Alteration of the discontinuity walls; g. Minerals present in the discontinuity walls. o Weathering state of discontinuities. o Aperture of the discontinuities. o R-values taken from the intact samples of each lithology units. <ul style="list-style-type: none"> o Intact Rock Strengths (IRS) derived from the weighted R-values of intercepted lithologies in the run. <p>Logging was carried out both qualitatively and quantitatively. Logs recorded lithology, oxidation intensity, hydrothermal alteration, mineralization, sulphide types, recovery, density as well as structural and vein orientation relative to oriented core to calculate dip and plunge of veins, faults, joints and breccias. Percentages of veining and sulphide content were also noted.</p> <p>All diamond drill cores were cleaned, clearly marked with drill hole identification and interval from beginning to end before being photographed. Sometimes photographed wet and dry, prior to being logged by geologists. All Menzies, NBG and Besra core photos were collated electronically and indexed.</p> <p>For Menzies, NBG and Besra 100% of the recovered core and RC drill chips, were properly logged and sampled.</p> <p>In 2010, CPs from TMCSA reviewed historic core and rock chips; re-logged and re-interpreted the relevant logs as necessary in addition to core descriptions in the drill logs and checked them against the lithological data entered into the database. TMCSA's documented observations noted that all pre-2010 core were logged with adequate geological and lithological descriptions, sample intervals, and correlated to assay data.</p> <p>From 2010 until 2017 CP, Graeme Fulton (TMC part of TMCSA), as General Manager of Bau Project, oversaw the drilling programs and compliance and ensured best logging practices and protocols were adhered to.</p> <p>From 2021 moving forward CP, Kevin Wright, as Project Manager of Bau, oversaw the drilling programs and compliance and ensured best logging practices and protocols were adhered to.</p> |
| | <p>The total length and percentage of the relevant intersections logged.</p> | |

| Criteria | JORC Code explanation | Commentary |
|---|---|---|
| Sub-sampling techniques and sample preparation | <p>If core, whether cut or sawn and whether quarter, half or all core taken.</p> <p>If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry.</p> | <p>BESRA. HQ core is sampled at 1m intervals. Core is sampled by splitting in half using a core saw. Samples and sample ticket are placed in numbered calico bags and sent to SGS Kuala Lumpur for sample prep and analysis. Duplicate samples are collected every 15 samples. Results of duplicate samples to date show a good correlation.</p> <p>Pre-1993 BYG/Gencor/RGC. BQ, NQ and HQ core was split using hammer and chisel using a solid steel frame /tube to hold the core during splitting. Assaying was conducted on site at the Tai Parit/Bukit Young mine laboratory in Bau with check assays conducted at other commercial labs outside Sarawak.</p> <p>1993 – 2000 Menzies. NQ and HQ cores were sampled at 1m intervals in mineralization and 4m intervals outside mineralization. 1m intervals were split in half using a core saw. 4m intervals were sampled using a core grinder “filleting” machine. 1m samples were dried and prepared on site using Menzies on site preparation lab.</p> <p>2005-2012 NBG. Core was sawn by diamond “Clipper” saw or split (where too soft to cut) into halves, with one half sent for analysis and the remaining labelled and retained for future reference. To prevent bias, the geologist logging the core supervised core cutting and ensured that the core was cut along the apex of any veins or significant mineralized structure.</p> <p>The geologists filled out standard instruction forms for the SGS analytical laboratory and the samples were delivered to the SGS sample preparation and processing facilities.</p> <p>CP, Kevin J. Wright has reviewed the SGS Bau sample preparation, fire assay and AA facility, process and equipment as well as the SOPs used by the SGS laboratory at BYG, and he is satisfied that due care and attention to precision and minimal contamination and loss of sample were executed to best industry standards.</p> <p>1993 – 2000 Menzies. RC samples were collected in plastic bags at 1m intervals from the cyclone (~25kg). Samples were split using a 4-inch diameter tube “spear” and placed into another 1m sample bag from which a second split was collected using a 2-inch spear. These second splits were composited into 4m intervals of around 1 to 4 kg from which 30g to 50g was used. All sample bags were appropriately labelled, ticketed and documented. When composite results assayed</p> |

| Criteria | JORC Code explanation | Commentary |
|----------|--|--|
| | <p>For all sample types, the nature, quality and appropriateness of the sample preparation technique.</p> <p>Quality control procedures adopted for all sub-sampling stages to maximise the representiveness of samples.</p> <p>Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling.</p> | <p>greater than 0.5 Au g/t, the original 1m samples were re-assayed. Most of the RC drilling at Jugan and Bekajang was shallow (<150m) and samples dry.</p> <p>At Bekajang, mineralization is finely disseminated throughout the host rock and the sample methodologies and sizes are considered appropriate for the style of mineralization.</p> <p>Besra and NBG core holes were sampled and assayed on nominal 1m intervals, except at geological or lithological boundaries. Historically, holes were sampled at 1.5 and 2m intervals. These longer run intervals make up approximately 5-10% of the total drilled metres.</p> <p>Where possible half-core was routinely cut along the same side of the re-oriented core.</p> <p>Post 1992. Samples of half core were routinely cut in half again (quartered) to create a duplicate sample for check assaying.</p> <p>1993 – 2000 Menzies. At regular intervals field duplicates of 1m RC samples were collected using 4” PVC spears.</p> <p>For any 4 x 1 metre RC composite samples that assayed > 0.5 g/t gold the corresponding 1 m samples were assayed. There was generally a very close correlation between the 4m composite sample assay and the average of the four 1m samples that made up the composite.</p> <p>NBG and Besra introduced industry standard protocols for QC by inserting certified standards, blank samples, umpire sampling, field duplicates from the coarse crushed material and preparation duplicates from the pulverized splits. In addition, SGS supplied NBG with an analysis, on a monthly basis, of the laboratory’s performance with respect to their own internal QC procedures. NBG/Besra’s standard sampling procedures for RC rock chips with insertion of standards, blanks and duplicates, are applied in the same manner as for drill core. Standard “second split/coarse split” and pulp duplicates were introduced into the sample stream for the laboratory assays. The results returned were analysed</p> |

| Criteria | JORC Code explanation | Commentary |
|----------|-----------------------|---|
| | | <p>providing an understanding of the proportions of the variance introduced and at this stage to optimise, and/or improve the process.</p> <p>Core sample intervals were selected through geology and mineralization logging, and assigned numbers, as well as insertion of standards, blanks and duplicates for representative in-situ sampling.</p> <p><u>Pulp Duplicates</u></p> <p>NBG and Besra's QC procedure included pulp duplicates retrospectively analysed at ten sample intervals from the database and assigned a unique number to related back to the primary sample number.</p> <p>Logarithmic Correlation Original of Original and Laboratory and Laboratory Repeat Samples, in Section 11, Sampling-Assaying, of the Pre-feasibility Study 2013 illustrates the results for re-sampled duplicates Vs laboratory original duplicates. The ideal trend line for a perfect duplicate Vs original sample result are almost identical.</p> <p>Lower grades limits show sample dispersion for lesser grade replication of the original samples. The higher variation of duplicate Vs original sample grades is within the detection limit and considered appropriate.</p> <p><u>Field Duplicates</u></p> <p>Integral to sampling QC for sample reproducibility, crushing homogenization and gold distribution a duplicate from every 10th sample was taken from the split after the second crushing to a nominal P80 -4mm whole sample. Each field duplicate is assigned a unique sample number in the sample stream for each batch.</p> <p>Log-log Plot graphs for Field Duplicates for the drilling completed at Jugan since 2005 are presented in The Pre-feasibility Study 2013, Section 11, Sampling – Assaying.</p> <p>Comparison of the field duplicate plots shows that correlation coefficients for Jugan are close to one.</p> <p><u>Preparation Duplicates</u></p> <p>Duplicate from every 10th sample was taken from the split after pulverizing a nominal P80 -75 microns for sample reproducibility, crushing homogenization at the fine grinding and gold distribution and information on sampling for the fire assay by laboratory personnel and other factors like nugget effect by overgrinding etc.</p> |

| Criteria | JORC Code explanation | Commentary |
|--|---|---|
| | <p>Whether sample sizes are appropriate to the grain size of the material being sampled.</p> | <p>Log-log Plot graphs for Preparation Duplicates for Jugan, are presented in The Pre-feasibility Study 2013, Section 11, Sampling - Assaying. Comparison of the preparation duplicate plots shows that correlation for Jugan are close to one.</p> <p><u>Laboratory Duplicates</u> QC procedure also monitored duplicate assays conducted by SGS on NBG's samples also shown in a Log-log Plot, SGS Duplicates Section 11, Sampling - Assaying showed a correlation coefficient of 0.98.</p> <p>At Jugan, mineralization is finely disseminated throughout the host rock. Samples sizes are considered appropriate for this style of mineralization. At Bekajang mineralisation is associated with alteration textures and disseminated within polymetallic sulphides within veins, stylolites, stockworks and fractures.</p> |
| <p>Quality of assay data and laboratory tests</p> | <p>The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.</p> | <p>BESRA. Half core samples have been analysed by SGS an accredited lab situated in Kuala Lumpur. All samples are crushed to 90% passing 2mm then a 250g split pulverized to 85% passing -75 microns (PRP87). Samples are analysed for gold by 50g charge fire assay (FAA505) and subject to 4 acid (total) digest followed by ICP-OES (ICP40Q) analysis for 24 trace elements.</p> <p>Gencor and RGC used their own protocols of duplicates, standards, blanks and umpires that were to industry standards of the 1980's. TMCSA stated that Menzies had rigorous QC protocols and all historic QC values available were evaluated.</p> <p>RGC and Gencor used the BYG mine lab pin part, but also commercial labs and their implemented their own QC systems.</p> <p>Menzies used Assaycorp initially in Australia and then in Kuching, Sarawak as well as McPhar (Manila), Analabs and Inchape for umpire assaying and QC.</p> <p>Au Fire Assay was conducted using a 50g charge with an AAS finish; SGS-FAA505 detection limit of 0.01 ppm. Fire assay is a complete gold analysis and is considered appropriate for the style of mineralization.</p> <p>Other elements (23) were analysed by SGS - ICP12S, IMS12S, AAS12S & CSA06V; where values exceed detection limit these were analysed using AAS42S.</p> <p>This suite did not initially include sulphur which was added late in the program to provide geo-metallurgical information.</p> |

| Criteria | JORC Code explanation | Commentary |
|----------|---|---|
| | <p>For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.</p> <p>Nature of quality control procedures adopted (e.g.</p> | <p>Total sulphur values above 2.5 % were determined by method CSA06V utilising high temperature combustion with Infrared measurement. Arsenic values above 0.5 % were determined by AAS.</p> <p>All the sample data for the 2010/12 programs were assayed initially by SGS either in Perth and/or later at the new BYG onsite SGS ISO 17025 compliant laboratory, conducting data verification and QC procedures on the assay data.</p> <p>NBG also conducted QC and verification procedures on the data. All sample data and returns were stored electronically and in hardcopy for future reference and checking. One blank was submitted with every batch of around, up to one hundred samples. Standards were inserted for every thirty samples.</p> <p>Umpire samples were not routinely run during the drill program. At Jugan all holes drilled by NBG and assayed at Mineral Assay & Services (MAS), Bangkok were re-assayed by ALS in Orange, NSW, Australia, an accredited laboratory and used as an umpire population to identify any major precision and accuracy issues with MAS. Some selected samples were also checked at SGS Waihi, New Zealand.</p> <p>CP, Kevin J. Wright has not reviewed any of the above identified laboratory preparation process used at that time and the proper implementation of otherwise sound SOPs by the laboratory have not been verified.</p> <p>No geophysical tools, spectrometers, handheld XRF units, etc were used in the analysis of the cores. Lab techniques used are described above.</p> <p>BESRA has a comprehensive QA/QC control program in place for its sampling procedures. Certified standards and blanks have been inserted into the sample stream at a ratio of 1 in 8 samples. One in 15 samples is a field duplicate and 1 in 15 samples is a lab duplicate (pulp or coarse crush material).</p> <p>All Batches (20 samples) of samples for the 2021-2022 campaign have passed QAQC checks which have considered, blanks, CRM standards, Field Duplicates, Lab Pulp Reject and Lab Coarse Rejects using industry accepted methods. Lab QAQC data was also reviewed.</p> <p>Drill core samples were analysed at SGS ISO certified geochemical lab in Kuala Lumpur, Malaysia. SGS insert their own CRM standards, blanks and run lab</p> |

| Criteria | JORC Code explanation | Commentary |
|----------|--|---|
| | <p>standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (i.e. lack of bias) and precision have been established.</p> | <p>duplicates for their own internal quality controls.</p> <p>NBG sourced certified geochemical standards from Rocklabs, New Zealand which were inserted into the sample stream at a ratio of 1:30. A variety of standards were used of different grades.</p> <p>NBG introduced industry best practices for QC procedures involving the insertion of certified standards, (e.g. Rocklabs SE58, SG56, SK52, SN60, and SG40 & SG50), blanks, umpire sampling, field and laboratory duplicates from the coarse crushed material and preparation duplicates from the pulverized splits. QC control samples were inserted at a nominal interval of 1 in 10 samples, except for blanks and standards which are inserted at 1 in 30 samples.</p> <p>TMCSA stated that most of the standards performed reasonably well reporting plus or minus 5% within the expected based on the 95 percentiles.</p> <p>SGS also insert its own duplicates, blanks and standards and reported these in its monthly analysis, siting their own internal QC procedures which included percentage passing/not passing 75µm with associated duplicate assays in the Au assay return. Log-log plots of SGS laboratory duplicates by TMCSA showed an acceptable correlation coefficient of 0.9848 for precision.</p> <p>In NBG's quality control procedure, duplicates of pulps were retrospectively analysed at intervals of ten (10) samples from the NBG database. Duplicate samples were assigned unique numbers that could be related to the primary sample number and tracked.</p> <p>NBG used logarithmic plots of the duplicates verses the laboratory duplicates which showed the ideal trend for a perfect original-duplicate sample result, derived from the equation $y=mx+b$ where m is the slope, which is equal to one, and b is the y-intercept (equal to the value of y when x is zero).</p> <p>Sample points for the duplicates showed a good correlation between the original and replicate samples. The distribution closely patterned the ideal linear trend line. Grades in the lower limits, however, showed more sample dispersion signifying lesser replication of grades of the original samples. The higher variation between the original and duplicate grades of samples near and within the detection limit zone can be considered normal.</p> <p>The QC elements of the Pre-feasibility Study 2013 did not identify that the integrity of the test work and assay results were significantly impacted by</p> |

| Criteria | JORC Code explanation | Commentary |
|----------|--|--|
| | <p>verification, data storage (physical and electronic) protocols.</p> | <p>off data (verified and validated) is stored in a secure CAE/Datamine Fusion database.</p> <p>1993 – 2000 Menzies, drilling field and logging records were transferred from hard copy sheets to the database by the geologist responsible. The database had verification protocols and security measures in place to minimize data entry errors. Digital reports from the assay labs were merged with drill hole data by the database manager. Hard copy assay certificates were kept in the Bau company office for reference. Databases were stored on multiple computers and backed up regularly.</p> <p>NBG stored all historic hard copy records including dispatch sheets, original signed assay result sheets, and geological logs on the site office in Bau. TMCSA reviewed several original surface and underground channel sampling maps and sections and documented that they found them adequate for resource estimation where survey control could be verified. Where data could not be verified, it was excluded from the database. TMCSA stated that analyses of data used in the resource estimation showed little or no difference in results with or without these samples and deemed appropriate to use.</p> <p>They identified field duplicates within the database. Whilst variations existed on a sample by sample comparison, TMCSA stated that the overall results they stated were nevertheless acceptable.</p> <p>NBG logging was entered directly into electronic spreadsheets, containing data validation routines and code tables and uploaded to master spreadsheet and subsequently uploaded to a fully integrated GeoMIMS platform with further data and code validation and checking. Data was transferred twice daily to the server. Historic data on hardcopy log sheets were captured on Excel spreadsheet format, validated and checked by TMCSA.</p> <p>Data verification was carried out by TMCSA on the primary data. Access Database on a project-by-project basis and recent data not in current database, e.g. NBG data.</p> <p>Checked collar surveys against original survey data sheets, duplications and omissions.</p> <p>Checked assays in database against original data logs for BYG, Menzies, RGC and Gencor.</p> |

| Criteria | JORC Code explanation | Commentary |
|---------------------------------------|--|---|
| | <p>Discuss any adjustment to assay data.</p> | <p>Compiled existing Menzies drill assay database, using original primary data laboratory assay certificates and/or from drill logs, including fire, roasted fire assay, and AAS, roasted AAS. Compared with data in Access database, corrected omissions, errors etc., and derived an accepted interval value resource modelling. Check geological log codes on Access database, on project-by-project basis. Modified codes where necessary; developed consistent coding system based on the existing Menzies coding system. Input data from NBG hard copy logs into new database for each project. Overall 1,614 drill holes within the resource areas were verified in terms of collar, survey, geology, density, assay values and intervals, including validation of 63,694 drill hole assay records.</p> <p>Issues including missing assay data, missing drill collars, miss-plotted drill holes, different drill holes with same collar and survey data, etc., were systematically reviewed, rectified where possible or discarded if not.</p> <p>From the database validation carried out, TMCSA stated that it was satisfied with the data integrity used for the resource estimation.</p> <p>Database validation was conducted regularly and when the resource definition began, used the standard mining software packages (Datamine/CAE Mining) tools. Following reviews and audits of available sampling and assay data by company staff and consultants, no justification was apparent to warrant adjustment of assay data.</p> |
| <p>Location of data points</p> | <p>Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.</p> | <p><u>Drill Hole Collars</u></p> <p>BESRA, drill hole collars are initially located using handheld GPS. Coordinates are WGS84 UTM Zone 49. Once completed, hole collars are preserved by constructing concrete plinths. Final collar locations are surveyed by a licensed surveyor to cm accuracy.</p> <p>All hole collars drilled by NBG before 2010 were surveyed by Resource Surveys Services, registered in Kuching, Sarawak using theodolite or total station. Most of the drill holes were resurveyed and checked by Resource Surveys Services and found to be within reasonable survey tolerances, with outsiders being adjusted to the re-surveyed value.</p> <p>Subsequent NBG hole collars were surveyed by registered surveyors using differential GPS and/or total station and recorded in the database. All surveys are based on registered and recognised survey stations in the area.</p> |

| Criteria | JORC Code explanation | Commentary |
|----------|-----------------------|---|
| | | <p>In 2010 TMCSA inspected a population of NBG drill hole locations and found the collars set in concrete with the drill hole number, in addition to depth, declination, control pegs, and survey control start, and completion date recorded. A selection of drill holes was checked with GPS identifying small discrepancies of the surveyed positions in the database consistent with accuracy limits of the GPS.</p> <p>Menzies drill holes were also surveyed and converted from the local grid verified by registered surveyors. These drill hole collars were cross-checked where available and according to TMCSA are within reasonable tolerances and TMCSA expressed a greater level of confidence in drill hole locations for all phases of past work than was previously available.</p> <p>During the NBG 2010, 2011 and 2012 drilling programs and field work, all historic drill holes were resurveyed, and their coordinates updated where applicable. Where original records or information was at hand the original coordinates were compared to the current coordinates and verified. Some of these were in other recognised coordinate systems allowing the update of drill holes and other data, particularly those in local grid coordinates.</p> <p>Updated topographic data was sourced from Malaysian government accredited aerial survey agents by registered surveyor, Resource Surveys. This topographic information was based on radar aerial surveys and has an elevation accuracy of 1-5m depending upon vegetation cover. This topography covered all the areas of interest for the Bau Project. Local survey updates were incorporated where applicable.</p> <p><u>Down Hole Surveys</u></p> <p>BESRA. Down hole surveys were conducted at 20m intervals using a Cameq 'ProShot' electronic multi-shot camera.</p> <p>NBG drilling. All drill core, where geological conditions allowed, were oriented at the end of each 3-metre run. Early in the program this was achieved by an orientation spear and then progressed to the use of an electronic 'OriShot' orientation device. Drillers marked the base of the drill core and base line of the core axis at the end of the run. This was checked by the NBG site geologist for accuracy and consistency.</p> |

| Criteria | JORC Code explanation | Commentary |
|---|---|---|
| | <p>Specification of the grid system used.</p> <p>Quality and adequacy of topographic control.</p> | <p>For orientation, all drill holes were initially routinely surveyed with a HKCX single shot then replaced by a Camteq 'ProShot' electronic multi-shot down hole camera.</p> <ul style="list-style-type: none"> • Readings were taken every 25m down hole for all holes and surveyed at termination. Orientation data was collected electronically with an Orishot orientation device routinely at the end of each HQ drill run where it was judged usable information could be obtained. Drill runs normally ran with core barrel lengths of 1.5m and 3.0m, sometimes 6m. Orientation data was recorded electronically to prevent transcription errors. • Down hole surveys were checked mathematically and visually in the database, and in 3D in the CAE Mining Studio geological and mining software package. Any surveys with recorded errors of unacceptable deviations were excluded from the down hole survey database. • Historic drill holes did not have down hole surveys done, only drill hole orientation surveyed at the collar. Because most of the holes were shallow (<100m) and vertical, according to TMCSA any deviation was considered minor. • Co-ordinates of individual samples in 3D was appropriately determined for and consistent with the needs of Mineral Resource estimating. <p>The WGS'84 datum UTM zone 49 coordinate system is used.</p> <p>Precision Aerial Surveys, Kuching has produced a digital elevation model (DEM) of the Bau goldfield accurate to 1-2m in height.</p> |
| <p>Data spacing and distribution</p> | <p>Data spacing for reporting of Exploration Results.</p> <p>Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.</p> | <p>Drill holes reported in this release are part of an infill drill program designed to increase drill hole density and confidence in the resource category. Drill spacing across the Bekajang resource ranges from 25 to 50m spacings.</p> <p>The drill hole collar spacing, corresponding data spacing, geological interpretation and assigned gold grades is considered sufficient and appropriate for Mineral Resource and Ore Reserve estimation procedure(s). Once the current drill program has been completed and assays received, an updated mineral resource estimate will be calculated.</p> |

| Criteria | JORC Code explanation | Commentary |
|--|---|---|
| | Whether sample compositing has been applied. | Sample compositing has only been done for intervals outside the zone of mineralization. |
| Orientation of data in relation to geological structure | <p>Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type.</p> <p>If the relationship between the drilling orientation and the orientation of key mineralized structures is considered to have introduced a sampling bias, this should be assessed and reported if material.</p> | <p>The zone of mineralization at Bekajang varies from flat-lying to moderately dipping. Holes have been drilled at dips ranging from vertical to -40 degrees, generally aimed to intersect the zone of mineralization perpendicular to its dip and strike of the bedding or structural controls.</p> <p>The drilling orientation is considered appropriate for sampling the principal mineralization orientation. Sufficient data density exists, and enough drill core logging, detailed mapping and statistical analysis has been done to consider sampling to be unbiased.</p> |
| Sample security | The measures taken to ensure sample security. | <ul style="list-style-type: none"> • BESRA. Each day cores placed into trays by drillers are transported in a built for purpose secured cage by staff to the Besra Bau office compound where logging and sampling takes place. The office is manned during the day and locked and patrolled by security at night. • Core samples are shipped by express courier with shipment tracking and chain of custody to the SGS lab in Kuala Lumpur. • All BYG, Gencor, RGC, Menzies and NBG drill cores were logged, sampled and stored in sheds at the Bukit Young mine site. The mine site was a secure compound. • Menzies RC samples were sampled on site during drilling and the 1m samples and 4 metres composites brought back to the Bukit Young mine site for storage prior to shipment to the Assaycorp lab in Kuching. • NBG, since 2007, all drill core was moved from drilling sites to the secure sample preparation facilities in Bau as soon as practical by geological staff. • All drill core and RC chips were stored at the core shed in Bau, along with sample pulps and coarse rejects. • The core logging and sample preparation areas were manned during working hours and had security patrols at night. Samples were stored in a fenced, locked and guarded core yard. • Only authorized NBG personnel were allowed access to the SGS sample preparation and laboratory areas and release of data could only come from the |

| Criteria | JORC Code explanation | Commentary |
|---------------------------------|--|---|
| | | <p>authorized laboratory manager to identified, authorized senior personnel at NBG.</p> <ul style="list-style-type: none"> • At the NBG Bau preparation area, all samples were packaged in secure cloth bags and taken over to the Bau SGS laboratory where samples were recorded, batch numbers assigned and passed into SGS's system. Samples were stored in a secure and locked area specifically for NBG samples. • NBG sample dispatch and SGS batch numbers were used for track and cross-checking through a Chain of Custody protocol. • For "off-shore" analysis, the split samples for Fire Assay were retained at SGS, while the splits for ICP were sealed in plastic bags, received in Kuching by NBG staff accompanied with sample dispatch sheets and bills of lading, and copies retained with the sample ledger following a Chain of Custody protocol. • NBG samples were air freighted using DHL to the MAS laboratory in Bangkok, Thailand or other laboratories as appropriate, and SGS in Bau in 2012. The laboratory was required to notify NBG if the samples did not arrive with the NBG seals intact and to retain all seals so that a probable Chain of Custody would be available. • Information regarding sample security, submission, storage procedures, Chain of Custody are described in Section 11, Sampling - Assaying of the Pre-feasibility Study 2013. |
| <p>Audits or reviews</p> | <p>The results of any audits or reviews of sampling techniques and data.</p> | <p>Exploration data in this release has not been the subject of any audit or review. TMCSA used all NBG original signed assay sheets from its programs extensively for checking and validating the databases. They checked these against physical drill core from current and historic drill holes.</p> <p>Historic data was audited in 2010 by TMCSA which noted that no matters of a serious nature, or nature likely to impair the validity of the sampling data and any subsequent use in the Mineral Resource estimates or Ore Reserve work.</p> <p>TMCSA wrote that it was confident the sample data had been verified to an acceptable level of confidence. Issues remained with some of the early fire assay data from the BYG site laboratory when converting from pennyweights to grams, and with the background/ detection limits used. TMCSA took the approach that with early fire assay data issues, AAS data was applied instead. Later assaying by the BYG site laboratory was independently checked by RGC and Menzies and issues identified, remedied or other independent and certified laboratories used.</p> |

| Criteria | JORC Code explanation | Commentary |
|----------|-----------------------|---|
| | | <p>SGS conducts its own internal audits and reviews which are relayed to the COO of Besra.</p> <p>NBG used MAS in Thailand and ALS in Australia and TMCSA's investigations show this sample data to be valid.</p> <p>CP, Kevin J. Wright had not reviewed the audits at that time and the otherwise findings of the audits have not been verified.</p> <p>CP, Kevin J. Wright has reviewed a population of the SGS assay certificates.</p> <p>According to TMCSA, previous validation and review of the historic data was conducted by a number of parties including Snowden & Associates, Australia and Ashby Consultants, New Zealand with no material problems being raised.</p> |

Section 2 Reporting of Exploration Results

(Criteria listed in the preceding section also apply to this section.)

| Criteria | JORC Code explanation | Commentary |
|--|--|---|
| Mineral tenement and land tenure status | Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings. | <p>Besra is in a consortium with a Malaysian group with Bumiputra interests that owns rights to consolidated mining tenements covering much of the historic Bau goldfield in Sarawak, East Malaysia. Besra's interests in the Bau Gold Project are held through its direct and indirect interests in North Borneo Gold Sdn Bhd ("NBG"). Besra's 100% owned subsidiary - Besra Labuan Ltd ("Besra Labuan")- acquired its interest in NBG, which owns rights to the mining tenements covering the area of Bau in accordance with various agreements the sale of shares as a result of which Besra's interests in NBG increased in September 2021 to 97.8% and its equity adjusted interest increased to 92.8%.</p> <p>NBG is governed by a joint venture agreement between the Company and a local Malaysian company, Gladioli Enterprises Sdn Bhd ("Gladioli") and is the operator of the Bau Gold Project. Gladioli is owned by the Ling family of Kuching. See attached summary.</p> <p><u>Structure</u></p> <p>The main joint venture company is NBG.</p> <p>NBG does not own the Tenements or any of the land owned by the Gladioli companies, it simply has rights to use such land and Tenements in accordance with the JV agreement. BML & Labuan or NBG can call for the Tenements to be transferred into the name of NBG, at which point those Tenements cease to be governed by the below structure.</p> <p><u>Operations</u></p> <p>NBG is to undertake all exploration and mining activities of the JV. Once a final feasibility study has been undertaken in relation to a particular area and a decision to mine has been made then a milling company ("Milling Company") will be incorporated to process the ore mined by NBG. The Milling Company is the company in which the "profit" of the JV will reside. As with NBG, the Milling Company will be owned by BML, BLL and Gladioli in the same respective shares as they own in NBG. In the alternative NBG can acquire the sole economic and beneficial ownership of the mined ore from Gladioli for RM10.00.</p> <p><u>Tenements</u></p> <p>The Tenements are currently held by the relevant Gladioli entities. BML/Labuan or NBG can at any time direct Gladioli to transfer the Tenements to NBG.</p> <p>The Tenements and the Specified Assets (being office buildings, the tailing dam, etc) are to be made available to NBG and the Milling Company in order to enable them to carry out</p> |

| Criteria | JORC Code explanation | Commentary |
|---|---|--|
| | | <p>their functions. Gladioli is required to pursue renewal of the Expired Licences with due diligence.</p> |
| | <p>The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.</p> | <p>For the duration of the JV the Gladioli companies must not sell, transfer or mortgage the Tenements other than with the consent of BML and Labuan. The Gladioli companies are obliged to maintain the Tenements in good standing and to renew the Tenements as and when required. All rentals and renewal fees are for the account of NBG.</p> <p>A potential impairment occasioned by the potential revocation of four Mining Leases (MLs) to facilitate the establishment of the Dered Krian National Park ("Park") has a near-term adverse impact upon the Bau project, however the bulk of the resources and reserve reduction remain external to the Park, so much of these potential reductions will be preserved under an excision proposal or new tenement applications if required. In which case the resources within these new MLs, external to the Park would contain the bulk of the resources and reserve of the four potentially revoked original MLs.</p> |
| <p>Exploration done by other parties</p> | <p>Acknowledgment and appraisal of exploration by other parties.</p> | <p>Gold was reported to have been exported from Bau from the 12th Century and gold mining activities have been reported from the Indonesian southern extension of the Bau District from as early as 1760.</p> <p>Mining in the Bau District dates from the 1820s, when Chinese prospectors exploited gold ores. Historical recorded gold production from the Bau area is 1.46 million Au Oz though the actual figure is thought to be 3-4 million Au Oz when production prior to 1898, unreported and recent production by Gladioli Group in the mid to late 1990's, is considered. In the late 1970's the Ling family consolidated tenements into a holding covering most of the prospective ground in the Bau Goldfield and re-opened the Tai Parit reporting production at 700,000 Au Oz, including 213,000 Au Oz by Bukit Young Goldmine Sdn Bhd ("BYG") between 1991 and 1997.</p> <p>A joint venture between BYG and RGC in 1985 conducted regional work around Bau as well as drilling several deep diamond drill holes at the Tai Parit mine and the central intrusive contacts.</p> <p>Minsarco, (subsidiary of GENCOR), carried out a Pre-feasibility study at Jugan in 1994. Resource estimates were prepared by Resource Services Group ("RSG") of Western Australia. BYG/ Menzies replaced Minsarco in 1996 acquiring a 55% interest in all tenements held by Gladioli.</p> |

| Criteria | JORC Code explanation | Commentary |
|----------------|---|--|
| | | <p>In 1996, BYG/Menzies initiated a Pre-feasibility study based on Bau, Jugan, Pejiru, Kapor and Bekajang deposits.</p> <p>Resource estimates for Jugan and Pejiru, were prepared and the subsequent estimate for Jugan reported significantly lower estimates than the 1994 estimate.</p> <p>BYG/Menzies continued with an extensive exploration program throughout the field with largely shallow RC drilling, but withdrew by 2001.</p> |
| Geology | Deposit type, geological setting and style of mineralization. | <p><u>Bau Project Geology</u></p> <p>The exposed rocks in the Bau district are dominated by a sequence of Late Jurassic to Early Cretaceous aged marine sediments. These comprise the lower Bau Limestone, unconformably overlain by the flysch sequence, Pedawan Formation dominated by shale. The oldest rocks in the Bau Goldfield are the Triassic-aged Serian andesitic volcanics that do not crop out but lie beneath the Bau Limestone. The Jagoi Granodiorite intrusive is thought to be co-eval with the Serian volcanics and it crops out SW of Bau on the Indonesian border.</p> <p>The Bau Goldfield deposits are characterized by four distinctive gold mineralization styles that exhibit both lateral and vertical geochemical and mineralogical zonation with respect to the Bau Trend intrusives:</p> <p>Sediment Rock-Hosted Disseminated Gold Deposits, e.g. Jugan; Bukit Sarin; Silica replacement (jasperoid) and open space siliceous breccias, e.g. Tai Parit; Bukit Young Pit, Bekajang; Mangano-calcite-quartz veins, e.g. Tai Ton; Pejiru, Kapor; Magmatic – Hydrothermal porphyry related deposits with/without calc-silicate skarn, e.g. Sirenggok, Say Seng, Ropih, Arong Bakit, and Juala West.</p> <p>Each of the 34 deposits or prospects contains one or more of these styles of mineralization covering an extent of 15km NE-SW by 7-8km NW-SE. The Bau Project geology and mineralization styles share characteristics with the Carlin Trend in Nevada, USA, hosted in calcareous sediments, host rock permeability important in mineralization, associated with deep faults, Tertiary-aged dacitic intrusives, solution collapse breccias and epithermal association.</p> <p>Similarities in Carlin mineralization style include silicic-argillic-carbonate hydrothermal alteration, fine grained arsenopyrite-pyrite Au common and similar trace element geochemistry, (As, Sb, Hg, Tl).</p> <p>Lateral zoning is related to the proximity of the Bau Trend felsic intrusives where they crop</p> |

| Criteria | JORC Code explanation | Commentary | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|-------------------------------|---|---|----------------|---------|----------|----------|-----|---------|-------|----------|----------|------------|------|-----|-----|------|----------|----------|------------|------|-----|-----|------|----------|----------|------------|------|-----|-----|-------|----------|----------|------------|------|-----|-----|-------|
| | | <p>out in the up domed portion of the Bau Limestone.</p> <p>The trend outward from intrusive centres is skarn/calc-silicate porphyry environment to silica rich mineralized breccias to silica replacement/calcite limestone contact to the more distal disseminated styles such as Jugan.</p> <p>Similar zonation patterns exist vertically within deposits such as Tai Parit, the only deposit mined to any depth. Previous exploration focused on the deposits in the central part of the field, less refractory as the deposits become more arsenopyrite rich further away from the intrusive centres.</p> <p>The zonation present is partly a function of the level of exposure and more distal deposits such as Jugan, Taiton, and Pejiru have excellent potential for locating mineralization similar to Tai Parit/Bekajang vertically beneath the current levels of exposure.</p> <p>The Bekajang deposit immediately southeast of the Bukit Young processing plant and has been traced for around 1,500 metres southeast and approximately 700 metres across strike. Several deposits are known to occur at the shale/limestone contact (“LSC target”) and are generally shallow dipping features with mineralisation developed in siliceous breccias within the shales on the contacts between shale and limestone. Part of the current program was to identify potential deeper mineralisation associated with the Bau Limestone (“Bau Deep”) targets.</p> <p>During exploration in 2011 several holes were drilled to test beneath the lake within the Bekajang tailings facility. These holes intersected vuggy quartz veins developed in limestone with gold mineralisation. In addition, a dacite porphyry dyke with strong quartz sericite alteration was intersected. This showed disseminated arsenopyrite needles developed marginal to microfractures, with a very similar paragenesis to the gold mineralisation at Sirenggok.</p> <p>Tai Parit has been mined since the 19th century by the British owned Borneo Company, and later acquired by the Bukit Young Goldmine company in 1970’s.</p> <p>Higher grade zone that plunges within the plane of the deposit correlates with a slight increase in silicification and sulphide content. Mineralization remains open at depth and on strike.</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Drill hole Information | <p>A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes:</p> <p>easting and northing of the drill hole collar</p> <p>elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar</p> | <p>Details of the Bekajang Follow Up Round Drill program</p> <table border="1"> <thead> <tr> <th>Drill Hole I.D</th> <th>Easting</th> <th>Northing</th> <th>Elev (m)</th> <th>Dec</th> <th>Azimuth</th> <th>Depth</th> </tr> </thead> <tbody> <tr> <td>BKDDH-31</td> <td>406388.2</td> <td>155739.247</td> <td>38.6</td> <td>-60</td> <td>315</td> <td>70.1</td> </tr> <tr> <td>BKDDH-32</td> <td>406393.4</td> <td>155713.745</td> <td>39.2</td> <td>-70</td> <td>315</td> <td>84.5</td> </tr> <tr> <td>BKDDH-33</td> <td>406407.6</td> <td>155757.097</td> <td>38.2</td> <td>-60</td> <td>315</td> <td>114.2</td> </tr> <tr> <td>BKDDH-34</td> <td>406422.2</td> <td>155682.053</td> <td>33.0</td> <td>-60</td> <td>315</td> <td>130.3</td> </tr> </tbody> </table> | Drill Hole I.D | Easting | Northing | Elev (m) | Dec | Azimuth | Depth | BKDDH-31 | 406388.2 | 155739.247 | 38.6 | -60 | 315 | 70.1 | BKDDH-32 | 406393.4 | 155713.745 | 39.2 | -70 | 315 | 84.5 | BKDDH-33 | 406407.6 | 155757.097 | 38.2 | -60 | 315 | 114.2 | BKDDH-34 | 406422.2 | 155682.053 | 33.0 | -60 | 315 | 130.3 |
| Drill Hole I.D | Easting | Northing | Elev (m) | Dec | Azimuth | Depth | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BKDDH-31 | 406388.2 | 155739.247 | 38.6 | -60 | 315 | 70.1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BKDDH-32 | 406393.4 | 155713.745 | 39.2 | -70 | 315 | 84.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BKDDH-33 | 406407.6 | 155757.097 | 38.2 | -60 | 315 | 114.2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BKDDH-34 | 406422.2 | 155682.053 | 33.0 | -60 | 315 | 130.3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| Criteria | JORC Code explanation | Commentary | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--|---|-----------|------------|--------------|-----|-------|-------|--|---------|--------|------|----|------------|----------|----------|-----|---|-----|-----|-------------|----------|-----|-----|-----|-----|-------------|----------|-----|---|---|---|-------------|----------|-----|---|------|-----|--------------|-----------|--|------|------|-----|--------------|-----------|--|------|-------|-----|-------------|-----------|-----|-----|------|-----|-------------|-----------|-----|-------|-------|-----|-------------|----------|-----|------|------|------|-------------|----------|-----|-------|-------|------|-------------|----------|-----|------|------|------|-------------|
| <p>dip and azimuth of the hole down hole length and interception depth hole length.</p> <p>If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.</p> | JUDDH-93 | BKDDH-35 | 406356.8 | 155767.490 | 36.2 | -70 | 135 | 99.8 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | JUDDH-94 | BKDDH-36 | 406394.0 | 155714.881 | 39.1 | -60 | 30 | 107.4 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | JUDDH-95 | BKDDH-37 | 406368.7 | 155676.906 | 31.8 | -60 | 30 | 131.4 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | JUDDH-96 | BKDDH-38 | 406418.8 | 155707.837 | 32.4 | -60 | 30 | 100.1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | JUDDH-97 | BKDDH-39 | 406374.6 | 155732.854 | 38.8 | -60 | 30 | 110.8 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | BKDDH-40 | 406368.8 | 155678.599 | 31.7 | -70 | 30 | 151.3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | BKDDH-41 | 406355.0 | 155656.896 | 31.4 | -75 | 30 | 94.4 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | BKDDH-42 | 406343.9 | 155689.286 | 31.3 | -70 | 30 | 72.1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | BKDDH-43 | 405945.47 | 155679.43 | 30.69 | -70 | 30 | 78.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | BKDDH-45 | 405896.89 | 155607.56 | 31.73 | -60 | 30 | 102.3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | All other drill holes have been previously reported. No drill holes from the current program have been excluded. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Data aggregation methods | <p>In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated.</p> <p>Where aggregate intercepts incorporate short lengths of high-grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.</p> <p>The assumptions used for any reporting of metal equivalent values should be clearly stated.</p> | <p>The table of significant intervals has used a 0.5 Au g/t cut-off, with a maximum of 2m internal dilution and no adjacent dilution included. Intervals are all 1m and so grades have not been length weighted or corrected for true width. Included intervals within these intervals are calculated at a 1.0 Au g/t cut-off. No top cut has been applied.</p> <table border="1"> <thead> <tr> <th>Hole ID</th> <th>Target</th> <th>From</th> <th>To</th> <th>Interval m</th> <th>Au (g/t)</th> </tr> </thead> <tbody> <tr> <td>BKDDH-12</td> <td>LSC</td> <td>0</td> <td>2.0</td> <td>2.0</td> <td>1.26</td> </tr> <tr> <td>BKDDH-12</td> <td>LSC</td> <td>4.0</td> <td>7.0</td> <td>3.0</td> <td>3.13</td> </tr> <tr> <td>BKDDH-13</td> <td>LSC</td> <td>0</td> <td>1</td> <td>1</td> <td>2.08</td> </tr> <tr> <td>BKDDH-13</td> <td>LSC</td> <td>7</td> <td>10.6</td> <td>3.6</td> <td>14.68</td> </tr> <tr> <td>Including</td> <td></td> <td>12.3</td> <td>13.6</td> <td>1.3</td> <td>37.00</td> </tr> <tr> <td>Including</td> <td></td> <td>9.00</td> <td>10.00</td> <td>1.0</td> <td>37.2</td> </tr> <tr> <td>BKDDH-14A</td> <td>LSC</td> <td>6.0</td> <td>12.7</td> <td>6.7</td> <td>3.34</td> </tr> <tr> <td>BKDDH-14A</td> <td>LSC</td> <td>21.00</td> <td>24.00</td> <td>3.0</td> <td>4.65</td> </tr> <tr> <td>BKDDH-15</td> <td>LSC</td> <td>13.7</td> <td>14.4</td> <td>0.70</td> <td>14.1</td> </tr> <tr> <td>BKDDH-16</td> <td>LSC</td> <td>18.00</td> <td>22.20</td> <td>1.42</td> <td>4.20</td> </tr> <tr> <td>BKDDH-18</td> <td>LSC</td> <td>2.40</td> <td>4.80</td> <td>2.40</td> <td>2.35</td> </tr> </tbody> </table> | | | | | | | | Hole ID | Target | From | To | Interval m | Au (g/t) | BKDDH-12 | LSC | 0 | 2.0 | 2.0 | 1.26 | BKDDH-12 | LSC | 4.0 | 7.0 | 3.0 | 3.13 | BKDDH-13 | LSC | 0 | 1 | 1 | 2.08 | BKDDH-13 | LSC | 7 | 10.6 | 3.6 | 14.68 | Including | | 12.3 | 13.6 | 1.3 | 37.00 | Including | | 9.00 | 10.00 | 1.0 | 37.2 | BKDDH-14A | LSC | 6.0 | 12.7 | 6.7 | 3.34 | BKDDH-14A | LSC | 21.00 | 24.00 | 3.0 | 4.65 | BKDDH-15 | LSC | 13.7 | 14.4 | 0.70 | 14.1 | BKDDH-16 | LSC | 18.00 | 22.20 | 1.42 | 4.20 | BKDDH-18 | LSC | 2.40 | 4.80 | 2.40 | 2.35 |
| Hole ID | Target | From | To | Interval m | Au (g/t) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BKDDH-12 | LSC | 0 | 2.0 | 2.0 | 1.26 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BKDDH-12 | LSC | 4.0 | 7.0 | 3.0 | 3.13 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BKDDH-13 | LSC | 0 | 1 | 1 | 2.08 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BKDDH-13 | LSC | 7 | 10.6 | 3.6 | 14.68 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Including | | 12.3 | 13.6 | 1.3 | 37.00 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Including | | 9.00 | 10.00 | 1.0 | 37.2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BKDDH-14A | LSC | 6.0 | 12.7 | 6.7 | 3.34 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BKDDH-14A | LSC | 21.00 | 24.00 | 3.0 | 4.65 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BKDDH-15 | LSC | 13.7 | 14.4 | 0.70 | 14.1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BKDDH-16 | LSC | 18.00 | 22.20 | 1.42 | 4.20 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BKDDH-18 | LSC | 2.40 | 4.80 | 2.40 | 2.35 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| Criteria | JORC Code explanation | Commentary | | | | | |
|----------|-----------------------|------------|----------|-------|-------|------|--------------|
| | | BKDDH-18 | LSC | 28.40 | 29.30 | 0.90 | 1.73 |
| | | BKDDH-18 | LSC | 33.00 | 35.00 | 2.00 | 1.19 |
| | | BKDDH-18 | LSC | 41.00 | 44.10 | 3.10 | 1.20 |
| | | BKDDH-19 | LSC | 38.7 | 43.0 | 4.3 | 0.81 |
| | | BKDDH-22 | LSC | 9.00 | 12.75 | 3.75 | 0.77 |
| | | BKDDH-23 | LSC | 1 | 9 | 8 | 1.35 |
| | | BKDDH-23 | LSC | 19.4 | 28 | 8.6 | 17.71 |
| | | including | | 19.4 | 20.0 | 0.6 | 30.4 |
| | | Including | | 20.0 | 20.8 | 0.8 | 103.0 |
| | | BKDDH-25 | Bau Deep | 65.0 | 68.7 | 3.7 | 0.86 |
| | | BKDDH-25 | Bau Deep | 71.6 | 76.0 | 4.4 | 0.82 |
| | | BKDDH-25 | Bau Deep | 86.0 | 86.90 | 0.9 | 3.17 |
| | | BKDDH-26 | Bau Deep | 48.0 | 50.0 | 2.0 | 0.73 |
| | | BKDDH-27 | LSC | 0 | 2 | 2 | 1.20 |
| | | BKDDH-27 | LSC | 8 | 17.7 | 9.7 | 7.09 |
| | | Including | | 15.1 | 16.0 | 0.9 | 39.3 |
| | | BKDDH-27 | Bau Deep | 40.3 | 42 | 1.7 | 8.81 |
| | | BKDDH-27 | Bau Deep | 43.6 | 45 | 1.4 | 4.49 |
| | | BKDDH-27 | Bau Deep | 53.9 | 56.1 | 2.2 | 3.90 |
| | | BKDDH-27 | Bau Deep | 58.4 | 71 | 12.6 | 22.91 |
| | | Including | | 60.5 | 61.0 | 0.5 | 209.0 |
| | | Including | | 61.0 | 62.0 | 1.0 | 64.0 |
| | | Including | | 62.0 | 63.0 | 1.0 | 15.9 |
| | | Including | | 63.0 | 64.0 | 1.0 | 31.8 |
| | | Including | | 64.0 | 65.0 | 1.0 | 22.3 |
| | | Including | | 67.0 | 68.0 | 1.0 | 14.1 |
| | | BKDDH-28 | LSC | 11.0 | 17.7 | 6.7 | 6.49 |
| | | Including | | 15.0 | 16.0 | 1.0 | 28.6 |
| | | BKDDH-29 | LSC | 26.0 | 35.0 | 9.0 | 3.22 |
| | | Including | | 28.0 | 30.0 | 2.0 | 6.5 |
| | | BKDDH-29 | | 36.0 | 39.0 | 0.55 | 3.0 |

| Criteria | JORC Code explanation | Commentary | | | | | |
|----------|-----------------------|------------|----------|-------|------|------|--------------|
| | | BKDDH-29 | | 40.0 | 44.0 | 4.0 | 0.87 |
| | | BKDDH-30 | LSC | 20.85 | 22.0 | 1.15 | 1.72 |
| | | BKHHD-30 | LSC | 25.0 | 26.0 | 1.0 | 2.25 |
| | | BKDDH-32 | LSC | 13.8 | 15.8 | 2 | 6.73 |
| | | BKDDH-32 | Deep Bau | 36.0 | 40.5 | 4.5 | 0.81 |
| | | BKDDH-32 | Deep Bau | 42.0 | 44.7 | 2.7 | 1.08 |
| | | BKDDH-32 | Deep Bau | 47.9 | 49.0 | 1.1 | 1.17 |
| | | BKDDH-32 | Deep Bau | 50.6 | 59.5 | 8.9 | 2.43 |
| | | BKDDH-33 | Deep Bau | 71.0 | 72.0 | 1.0 | 0.54 |
| | | BKDDH-34 | Deep Bau | 87.0 | 88.0 | 1.0 | 0.83 |
| | | BKDDH-36 | Deep Bau | 33.7 | 36.0 | 2.3 | 1.03 |
| | | BKDDH-36 | Deep Bau | 40.7 | 41.7 | 1.0 | 10.70 |
| | | BKDDH-36 | Deep Bau | 45.3 | 46.3 | 1.0 | 5.60 |
| | | BKDDH-37 | LSC | 6.9 | 8.00 | 1.10 | 6.25 |
| | | BKDDH-37 | LSC | 13.0 | 14.0 | 1.0 | 0.61 |
| | | BKDDH-37 | LSC | 14.6 | 17.0 | 2.4 | 0.81 |
| | | BKDDH-37 | Deep Bau | 32.0 | 34.0 | 2.0 | 0.73 |
| | | BKDDH-37 | Deep Bau | 36.2 | 41.3 | 5.1 | 2.31 |
| | | BKDDH-37 | Deep Bau | 45.9 | 50.0 | 4.1 | 1.67 |
| | | BKDDH-37 | Bau Deep | 51.7 | 60.0 | 8.3 | 1.33 |
| | | BKDDH-38 | LSC | 0.0 | 4.0 | 4.0 | 1.14 |
| | | BKDDH-38 | LSC | 6.8 | 8.0 | 1.2 | 1.22 |
| | | BKDDH-38 | LSC | 10.0 | 11.6 | 1.6 | 0.56 |
| | | BKDDH-38 | LSC | 15.0 | 20.5 | 5.5 | 3.60 |
| | | BKDDH-39 | Bau Deep | 44.0 | 46.8 | 2.8 | 0.66 |
| | | BKDDH-40 | LSC | 0.0 | 8.0 | 8.0 | 1.01 |
| | | BKDDH-40 | LSC | 9.00 | 10.0 | 1.0 | 0.51 |
| | | BKDDH-40 | Bau Deep | 31.5 | 35.3 | 3.8 | 2.05 |
| | | BKDDH-40 | Bau Deep | 38.3 | 39.3 | 1.0 | 1.89 |

| Criteria | JORC Code explanation | Commentary | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---|---|----------|-----------------|--------------|------|-----|-------------|----------|-----------------|------|------|-----|-------------|----------|------------|-----|-----|-----|-------------|----------|------------|-----|-----|-----|-------------|----------|------------|------|------|-----|-------------|----------|-----------------|------|------|-----|-------------|----------|-----------------|------|------|-----|--------------|----------|-----------------|------|------|-----|-------------|----------|-----------------|------|------|-----|-------------|----------|-----------------|------|------|-----|-------------|----------|------------|------|------|-----|-------------|----------|------------|------|------|-----|-------------|----------|-----------------|------|------|-----|-------------|----------|-----------------|------|------|-----|-------------|
| | | <table border="1"> <tr> <td>BKDDH-40</td> <td><i>Bau Deep</i></td> <td>40.7</td> <td>46.9</td> <td>6.2</td> <td>3.35</td> </tr> <tr> <td>BKDDH-40</td> <td><i>Bau Deep</i></td> <td>49.8</td> <td>58.3</td> <td>8.5</td> <td>2.12</td> </tr> <tr> <td>BKDDH-41</td> <td><i>LSC</i></td> <td>0.0</td> <td>3.0</td> <td>3.0</td> <td>2.62</td> </tr> <tr> <td>BKDDH-41</td> <td><i>LSC</i></td> <td>5.0</td> <td>8.9</td> <td>3.9</td> <td>1.58</td> </tr> <tr> <td>BKDDH-41</td> <td><i>LSC</i></td> <td>19.0</td> <td>20.7</td> <td>1.7</td> <td>1.72</td> </tr> <tr> <td>BKDDH-41</td> <td><i>Bau Deep</i></td> <td>29.5</td> <td>30.5</td> <td>1.0</td> <td>0.51</td> </tr> <tr> <td>BKDDH-41</td> <td><i>Bau Deep</i></td> <td>31.5</td> <td>32.9</td> <td>1.4</td> <td>14.21</td> </tr> <tr> <td>BKDDH-41</td> <td><i>Bau Deep</i></td> <td>35.3</td> <td>38.7</td> <td>3.4</td> <td>1.94</td> </tr> <tr> <td>BKDDH-41</td> <td><i>Bau Deep</i></td> <td>41.8</td> <td>42.9</td> <td>1.1</td> <td>2.38</td> </tr> <tr> <td>BKDDH-41</td> <td><i>Bau Deep</i></td> <td>44.1</td> <td>45.9</td> <td>1.8</td> <td>1.04</td> </tr> <tr> <td>BKDDH-42</td> <td><i>LSC</i></td> <td>14.8</td> <td>15.8</td> <td>1.0</td> <td>5.34</td> </tr> <tr> <td>BKDDH-43</td> <td><i>LSC</i></td> <td>19.0</td> <td>21.2</td> <td>2.2</td> <td>0.96</td> </tr> <tr> <td>BKDDH-43</td> <td><i>Bau Deep</i></td> <td>23.0</td> <td>31.7</td> <td>8.7</td> <td>1.66</td> </tr> <tr> <td>BKDDH-43</td> <td><i>Bau Deep</i></td> <td>35.0</td> <td>36.0</td> <td>1.0</td> <td>0.78</td> </tr> </table> | BKDDH-40 | <i>Bau Deep</i> | 40.7 | 46.9 | 6.2 | 3.35 | BKDDH-40 | <i>Bau Deep</i> | 49.8 | 58.3 | 8.5 | 2.12 | BKDDH-41 | <i>LSC</i> | 0.0 | 3.0 | 3.0 | 2.62 | BKDDH-41 | <i>LSC</i> | 5.0 | 8.9 | 3.9 | 1.58 | BKDDH-41 | <i>LSC</i> | 19.0 | 20.7 | 1.7 | 1.72 | BKDDH-41 | <i>Bau Deep</i> | 29.5 | 30.5 | 1.0 | 0.51 | BKDDH-41 | <i>Bau Deep</i> | 31.5 | 32.9 | 1.4 | 14.21 | BKDDH-41 | <i>Bau Deep</i> | 35.3 | 38.7 | 3.4 | 1.94 | BKDDH-41 | <i>Bau Deep</i> | 41.8 | 42.9 | 1.1 | 2.38 | BKDDH-41 | <i>Bau Deep</i> | 44.1 | 45.9 | 1.8 | 1.04 | BKDDH-42 | <i>LSC</i> | 14.8 | 15.8 | 1.0 | 5.34 | BKDDH-43 | <i>LSC</i> | 19.0 | 21.2 | 2.2 | 0.96 | BKDDH-43 | <i>Bau Deep</i> | 23.0 | 31.7 | 8.7 | 1.66 | BKDDH-43 | <i>Bau Deep</i> | 35.0 | 36.0 | 1.0 | 0.78 |
| BKDDH-40 | <i>Bau Deep</i> | 40.7 | 46.9 | 6.2 | 3.35 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BKDDH-40 | <i>Bau Deep</i> | 49.8 | 58.3 | 8.5 | 2.12 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BKDDH-41 | <i>LSC</i> | 0.0 | 3.0 | 3.0 | 2.62 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BKDDH-41 | <i>LSC</i> | 5.0 | 8.9 | 3.9 | 1.58 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BKDDH-41 | <i>LSC</i> | 19.0 | 20.7 | 1.7 | 1.72 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BKDDH-41 | <i>Bau Deep</i> | 29.5 | 30.5 | 1.0 | 0.51 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BKDDH-41 | <i>Bau Deep</i> | 31.5 | 32.9 | 1.4 | 14.21 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BKDDH-41 | <i>Bau Deep</i> | 35.3 | 38.7 | 3.4 | 1.94 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BKDDH-41 | <i>Bau Deep</i> | 41.8 | 42.9 | 1.1 | 2.38 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BKDDH-41 | <i>Bau Deep</i> | 44.1 | 45.9 | 1.8 | 1.04 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BKDDH-42 | <i>LSC</i> | 14.8 | 15.8 | 1.0 | 5.34 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BKDDH-43 | <i>LSC</i> | 19.0 | 21.2 | 2.2 | 0.96 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BKDDH-43 | <i>Bau Deep</i> | 23.0 | 31.7 | 8.7 | 1.66 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BKDDH-43 | <i>Bau Deep</i> | 35.0 | 36.0 | 1.0 | 0.78 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <p>No shorter length intervals have been aggregated. No metal equivalent values have been used</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Relationship between mineralization widths and intercept lengths | These relationships are particularly important in the reporting of Exploration Results. | <p>For the shallower dipping mineralized structures, the drill hole angle placement was selected to target both mineralization orientations, and intersections approximate the true width.</p> <p>To intersect the main mineralization trends at a high angle, holes were oriented to the extent possible normal to the mineralization's strike direction.</p> <p>These high angle drill holes produced longer down-dip intersections than the largely sub-vertical mineralized structure's true widths.</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | If the geometry of the mineralization with respect to the drill hole angle is known, its nature should be reported. | The Bekajang defined resource is focused on the LSC stratigraphic boundary located at depths of typically 5 to 35m and spatially oriented in a NNW-SSE directly paralleling surface mapped faults, traversing the northern flank of the Bekajang tailings dam. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| Criteria | JORC Code explanation | Commentary |
|---|---|---|
| | If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known'). | The mineral domains were constructed in 3D, hence true widths were considered. |
| Diagrams | Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views. | Figures have been included |
| Balanced reporting | Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results. | Balanced reporting has been carried out with intercepts classed as no significant gold values as well as significant gold values. In sections historical intervals are presented, as well intervals with no gold values for context for the current drill holes reported in the 2021-2022 program |
| Other substantive exploration data | Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances. | There are no other new meaningful or material exploration data to be reported. |
| Further work | The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling). Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive. | Drilling at the Bekajang Project is designed to extend the resource. Following the extremely high grade intercepts at both the LSC and Deep Bau Limestone levels a follow up round of follow up drilling will be undertaken to test between two alternate mineralisation concepts, including proof of concept drilling of the interpreted intrusive identified by the DIGHEM anomaly. Diagrams of these concepts are provided however at this time, the drill hole locations are still under consideration. |